

County Surveyor's Record, Douglas County, Oregon

15249

Subdivision of Section 11, T. 24 S., R. 6 W.,
Willamette Meridian, Oregon

CHAINS

Subdivision of Section 11, T. 24 S., R. 6 W.,
Willamette Meridian, Oregon

From the 1/4 sec. cor. of secs. 11 and 14.

N. 0° 10' E., on the N. and S. center line of sec. 11.

Ascend 20 ft. over gentle S. slope, through light timber and moderate undergrowth.

6.55 Spur, slopes NE.; desc. 123 ft. over NE. slope.

20.02 Creek, 2 lks. wide, course N. 80° E.; asc. 2 ft. over SE. slope.

20.07 Point for the center S 1/16 sec. cor. of sec. 11.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C \\ S\ 1/16 \left| S\ 11 \\ C \\ 1975 \end{array}$$

from which

A cedar, 13 ins. diam., bears N. 72° E., 300 lks. dist., mkd. CS 1/16 S11 BT.

A white fir, 8 ins. diam., bears S. 88° W., 66 lks. dist., mkd. CS 1/16 S.. BT.

Ascend 5 ft. over SE. slope.

23.85 Spur, slopes NE.; desc. 110 ft. over NE. slope.

35.40 Creek, 4 lks. wide, course S. 46° E.; asc. 10 ft. over SW. slope.

38.10 Dirt road, 18 lks. wide, bears NW. and SE.

40.14 Point for the center 1/4 sec. cor. of sec. 11, at intersection with the W. and W. center line.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 23 ins. in the ground, with brass cap mkd.

$$\begin{array}{c} C\ 1/4\ S\ 11 \\ 1975 \end{array}$$

from which

A white oak, 16 ins. diam., bears S. 43° E., 353 lks. dist., mkd. C 1/4 S11 BT.

A white oak, 16 ins. diam., bears N. 76° W., 330 lks. dist., mkd. C 1/4 S11 BT.

Ascend 115 ft. over gentle SW. slope.

51.20 Spur, slopes S. 5° E.; asc. 95 ft. over SE. slope.

60.25 Point for the center N 1/16 sec. cor. of sec. 11.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 27 ins. in the ground, with brass cap mkd.