

County Surveyor's Record, Douglas County, Oregon

15256

Dependent Resurvey of the South Boundary,
T. 20 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 32 ins. diam., bears N. 5° W.,
54 lks. dist., with scribe marks BT visible on
opened blaze.

A sawed fir stump, 29 ins. diam., bears S. 12° W.,
20 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 20 S R 5 W
1/4 $\frac{S\ 36}{S\ 1}$
T 21 S
1968

from which new bearing trees

A fir, 10 ins. diam., bears N. 33 1/2° W., 18 lks.
dist., mkd. 1/4 S36 BT.

A fir, 8 ins. diam., bears S. 24° W., 18 1/2 lks.
dist., mkd. 1/4 S1 BT.

N. 89° 42' W., beginning new measurement.

Descend 35 ft. over NW. slope.

4.55 Creek, 3 lks. wide, course N. 30° E.; asc. 320 fr.
over NE. slope.

9.20 Dirt road, 15 lks. wide, bears N. 7° E., and S. 7° W.

28.05 Ravine, drains N. 45° E.; asc. 115 ft. over NE. slope.

39.10 Spur, slopes N. 5° W.; desc. 10 ft. over NW. slope.

40.16 Point for the cor. of secs. 1, 2, 35, and 36, at proport-
ionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 20 S R 5 W
 $\frac{S\ 35\ | S\ 36}{S\ 2\ | S\ 1}$
T 21 S
1968

from which

A fir, 15 ins. diam., bears N. 33° E., 27 lks.
dist., mkd. T20S R5W S36 BT.

A fir, 10 ins. diam., bears S. 52° E., 28 lks.
dist., mkd. T21S R5W S1 BT.

A fir, 11 ins. diam., bears S. 54 1/2° W., 17 lks.
dist., mkd. T21S R5W S2 BT.

A fir, 8 ins. diam., bears N. 27° W., 24 lks.
dist., mkd. T20S R5W S35 BT.