

# County Surveyor's Record, Douglas County, Oregon

15259

Dependent Resurvey of the South Boundary,  
T. 20 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

N. 89° 10' W., bet. secs. 3 and 34.

Descend 70 ft. over NW. slope, along S. edge of old logged area, through dense undergrowth.

2.50 Creek, 2 lks. wide, course N. 10° W.; asc. 205 ft. over NE. slope.

28.45 Ridge, bears N. 20° E., and S. 20° W.; desc. 25 ft. over NW. slope.

31.50 Bottom of descent, slopes N.; asc. 40 ft. over NE. slope.

35.90 Spur, slopes N. 20° W.; desc. 155 ft. over NW. slope.

40.10 The 1/4 sec. cor. of secs. 3 and 34. remonumented by Vernon Tracy, Deputy Douglas County Surveyor, in 1965, with an iron post, 1 in. diam., firmly set, projecting 8 ins. above ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYORS OFFICE

	T 20 S	
	<u>S 34</u>	R
1/4	S 3	5
	T 21 S W	W
	1965	

from which the remains of the original bearing trees

A root hole, bears N. 34° W., 69 lks. dist., bears a down and decayed fir alongside, 16 ins. diam., no marks visible.

A shattered maple stump, 19 ins. diam., bears S. 43° W., 21 lks. dist., with scribe marks 1/4 visible in negative on overgrowth of decayed blaze.

and bearing trees mkd. by Tracy

A fir, 16 ins. diam., bears N. 33° W., 54 lks. dist., with healed double blaze.

A shattered maple stump, 17 ins. diam., bears S. 43° W., 25 lks. dist., with scribe marks BT visible on open blaze.

and a new bearing tree

A hemlock, 8 ins. diam., bears S. 41° W., 98 lks. dist., mkd. 1/4 S3 BT.

Add the marks, BLM 1967, to the brass cap.

---

N. 89° 47' W., beginning new measurement.

Descend 145 ft. over NW. slope.