

County Surveyor's Record, Douglas County, Oregon

15260

Dependent Resurvey of the South Boundary
T. 20 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

11.75 Ravine, drains N. 30° W.; asc. 70 ft. over NE. slope.

20.08 Point for the W 1/16 sec. cor. of secs. 3 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} W\ 1/16 \quad \frac{S\ 34}{S\ 3} \\ 1967 \end{array}$$

from which

A hemlock, 7 ins. diam., bears N. 64 1/2° E., 28 1/2 lks. dist., mkd. W 1/16 S34 BT.

A hemlock, 8 ins. diam., bears S. 22° W., 42 1/2 lks. dist., mkd. W 1/16 S3 BT.

Ascend 90 ft. over NE. slope.

26.50 Spur, slopes N.; desc. 50 ft. over NW. slope.

29.55 Ravine, drains N. 10° E.; aslo dirt road, 15 lks. wide bears NW. and NE., in a curve; asc. 100 ft. over NE. slope.

32.80 Dirt road, 15 lks. wide, bears N. 10° E. and S.

34.10 Spur ridge, bears N. 10° E. and S.; desc. 195 ft. over NW. slope.

40.16 The cor. of secs. 3, 4, 33, and 34, determined at record bearing and distance, from the remains of the original bearing trees:

A decayed fir stump, 29 ins. diam., bears S. 75° E., 39 lks. dist., no marks visible.

A root hole, bears S. 21° W., 128 lks. dist.

A root hole, bears N. 52° W., 5 lks. dist.

and trees of which I have no record

A decayed fir stump, 12 ins. diam., bears N. 56 1/2° E., 9 lks. dist., with fragmentary scribe marks visible on decayed blaze.

A decayed fir stump, 8 ins. diam., bears N. 24 1/2° W., 11 lks. dist., no marks visible.

A sawed fir stump, 25 ins. diam., bears N. 73° W., 32 1/2 lks. dist., with scribe marks D 6-24 J L 18 visible on opened blaze on butt portion of log lying nearby.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} T\ 20\ S\ R\ 5\ W \\ \frac{S\ 33\ | \ S\ 34}{S\ 4\ | \ S\ 3} \\ T\ 21\ S \\ 1967 \end{array}$$

from which new bearing trees