

# County Surveyor's Record, Douglas County, Oregon

15261

Dependent Resurvey of the South Boundary,  
T. 20 S., R. 5 W., Willamette Meridian, Oregon

**CHAINS**

A fir, 25 ins. diam., bears S. 86° E., 30 lks.  
dist., mkd. X at breast height and BT at base.

A fir, 20 ins. diam., bears S. 14° E., 67 lks.  
dist., mkd. T21S R5W S3 BT.

A fir 30 ins. diam., bears S. 33 3/4° W., 89 lks.  
dist., mkd. T21S R5W S4 BT.

A fir, 25 ins. diam., bears N. 23° W., 165 lks.  
dist., mkd. T20S R5W S33 BT.

No suitable tree available within limits in sec. 34.

Land, mountainous.  
Soil, rocky clay loam.  
Timber, fir, alder, maple, hemlock, cedar, chinquapin,  
and madrone; undergrowth, hazel, salal, Oregon grape,  
huckleberry, ceanothus, salmonberry, vine maple, black-  
berry, arrowwood, poison oak, and fern.

N. 89° 51' W., bet. secs. 4 and 33.

Descend 50 ft. over SW. slope, through heavy timber and  
dense undergrowth.

1.75 Creek, 3 lks. wide, course N. 55° W.; asc. 20 ft. along  
broken N. slope.

10.20 Ravine, drains N. 30° W.; asc. 220 ft. over NE. slope.

17.70 Spur, slopes N.; desc. 200 ft. over NW. slope.

26.05 Creek, 2 lks. wide, course N. 25° W.; asc. 160 ft. over  
NE. slope.

40.16 The 1/4 sec. cor. of secs. 4 and 33, determined at record  
bearing and distance from the remains of the original  
bearing tree:

A fir, 57 ins. diam., bears N. 10 1/2° W., 46 lks.  
dist., with scribe marks 1/4 S visible on opened  
blaze.

At the corner point

Set an iron pipe, 14 ins. long, 1 in. diam., 14 ins. in  
the ground. This point is located at the top of a road  
cut where it is impracticable to set a standard iron  
post. From which new bearing trees and reference monu-  
ments:

A fir, 10 ins. diam., bears N. 79° E., 182 lks.  
dist., mkd. 1/4 S33 BT.

A fir, 5 ins. diam., bears S. 7 3/4° W., 100 lks.  
dist., mkd. 1/4 S4 BT.

An iron post, 28 ins. long, 2 1/2 ins. diam., set 20  
ins. in the ground, for a reference monument,  
bears South, 25 lks. dist., with brass cap mkd.  
1/4 S4 RM 1967, and an arrow pointing to the corner.