

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the South Boundary,
T. 20 S., R. 5 W., Willamette Meridian, Oregon

15263

CHAINS

A fir, 8 ins. diam., bears S. 73° W., 90 lks.
dist., mkd. T21S R5W S5 BT.

Add the marks, BLM 1967, to the brass cap.

Land, mountainous.
Soil, rocky clay loam.
Timber, hemlock, fir, cedar, alder, maple, chinquapin,
and madrone; undergrowth, salal, hazel, arrowwood, ceano-
thus, huckleberry, Oregon grape, salmonberry, vine
maple, blackberry, rhododendron, poison oak, and fern.

N. 89° 49' W., bet. secs. 5 and 32.

Descend 115 ft. over SW. slope, through heavy timber and
dense undergrowth.

- 14.15 Ravine, drains S. 20° E.; asc. 25 ft. over SE. slope.
- 15.55 Dirt road, 20 lks. wide, bears S. 60° W., and N. 15° E.,
in a curve.
- 16.20 Top of ascent, slopes S.; desc. 40 ft. over SW. slope.
- 18.15 Dirt road, 20 lks. wide, bears N. 45° W., and S. 70° E.,
in a curve.
- 19.15 Bottom of descent, slopes S.; asc. 30 ft. over SE. slope.
- 20.40 Dirt road, 20 les. wide, bears S. 60° W., and N. 45° E.,
in a curve.
- 22.70 Top of ascent, slopes S.; desc. 25 ft. over SW. slope.
- 25.25 Ravine, drains S.; asc. 60 ft. over SE. slope.
- 29.75 Top of ascent, slopes S.; desc. 50 ft. over SW. slope.
- 32.40 Ravine, drains S. 5° W.; asc. 115 ft. over SE. slope.
- 37.75 Spur, slopes S.45° W.; desc. 25 ft. over SW. slope.
- 40.08 The 1/4 sec. cor. of secs. 5 and 32, remonumented by
Bruce R. Rogers, Deputy Douglas County Surveyor, in 1965,
with an iron post, 1 in. diam., firmly set, projecting
8 ins. above ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYORS OFFICE

	T 20 S	
1/4	S 32	R
	S 5	5
	T 21 S	W
	1965	

from which the remains of the original bearing trees

A sawed hemlock stump, 25 ins. diam., bears
N. 17° W., 35 lks. dist., with healed blaze.

A sawed fir stump, 30 ins. diam., bears S. 17° E.,
28 lks. dist., with fragmentary scribe marks
visible on opened blaze.

and bearing trees mkd. by Rogers