

County Surveyor's Record, Douglas County, Oregon

15264

Dependent Resurvey of the South Boundary,
T. 20 S., R. 5 W., Willamette Meridian, Oregon

CHAINS

A fir, 6 ins. diam., bears N. 47° W., 31 lks. dist., with scribe marks 1/4 S32 CS BT visible on open double blaze.

A cedar snag, 13 ins. diam., bears S. 21 1/2° W., 30 lks. dist., with scribe marks 1/4 S5 CS BT visible on open double blaze.

and a new bearing tree

A fir, 5 ins. diam., bears S. 39° W., 8 lks. dist., mkd. 1/4 S5 BT.

Add marks BLM 1967 to brass cap.

N. 89° 11' W., beginning new measurement.

Descend 30 ft. over SW. slope.

2.55 Bottom of descent, slopes S.; asc. 15 ft. over SE. slope.

4.75 Top of ascent, slopes S.; desc. 40 ft. over SW. slope.

7.35 Bottom of descent, slopes S.; asc. 85 ft. over SE. slope.

12.05 Ridge, bears N. 40° E. and S. 40° W.; desc. 150 ft. over NW. slope.

17.65 Bottom of descent, slopes NW.; asc. 40 ft. along N. slope.

23.50 Top of ascent, slopes N.; desc. 40 ft. along N. slope.

27.20 Bottom of descent, slopes N.; asc. 130 ft. over NE. slope.

36.90 Spur, slopes N. 10° W.; desc. 90 ft. over NW. slope.

39.99 The cor. of secs. 5, 6, 31, 32, remonumented by Milo E. Godfrey, eputy Douglas County Surveyor, in 1962, with an iron post, 1 in. diam., firmly set, projecting 14 ins. above ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYORS OFFFICE
T 20 S R 5 W
S 31 | S 32
S 6 | S 5
T 21 S
1962

from which the remains of the original bearing trees

A fir snag, 61 ins. diam., bears N. 18° E., 28 lks. dist., with scribe marks S R5W visible on opened blaze. (Record, 26 lks.)

A cedar snag, 32 ins. diam., bears S. 7° E., 32 lks. dist., with healed blaze.

A root hole, bears S. 60° W., 95 lks. dist., with a down and decayed hemlock alongside, 18 ins. diam., no marks visible.

A cedar, 40 ins. diam., bears N. 68° W., 10 lks.