

County Surveyor's Record, Douglas County, Oregon

15267

Dependent Resurvey of a Portion of the West Boundary,
T. 20 S., R. 5 W., Willamette Meridian, Oregon

CHAINS	
	(Restoring the 1854-55 survey by Harvey Gordon, Deputy Surveyor)
	From the cor. of Tps. 20 and 21 S., Rs. 5 and 6 W., heretofore described.
	N. 0° 19' E., bet. secs. 31 and 36, marking and blazing the true line.
	Descend 35 ft. along E. slope, through heavy timber and dense undergrowth.
3.	3.00 Abandoned dirt road, 20 lks. wide, bears S. 30° E., and N. 40° W.
	7.20 Ravine, drains S. 55° E.; asc. 160 ft. over S. slope, changing to SE. slope.
	25.70 Top of ascent, slopes E.; desc. 25 ft. over NE. slope.
	27.80 Bottom of descent, slopes E.; asc. 145 ft. over SE. slope.
	38.05 Unmaintained dirt road, 20 lks. wide, bears N. 75° E., and S. 75° W.
	40.35 The 1/4 sec. cor. of secs. 31 and 36, monumented by Milo E. Godfrey Douglas County Surveyor, in 1962, with an iron post, 1 in. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.
	DOUGLAS COUNTY SURVEYORS OFFICE T 20 S 1/4 S 36 S 31 R 6 W R 5 W 1962
	from which the remains of the original bearing tree
	A fir, 34 ins. diam., bears N. 23° E., 29 lks. dist., with scribe marks 4S visible on opened blaze.
	and bearing trees mkd. by Godfrey
	A hemlock, 15 ins. diam., bears S. 55° E., 27 lks. dist., with scribe marks 1/4 S31 DCS BT visible on open double blaze.
	A hemlock, 9 ins. diam., bears N. 63 3/4° W., 26 1/2 lks. dist., with scribe marks 1/4 S36 DCS BT visible on open double blaze.
	Add the marks, BLM 1967, to the brass cap.
	N. 0° 13' W., beginning new measurement.
	Ascend 35 ft. over S. slope.
	3.75 Ridge, divides Smith River and Siuslaw River drainage, bears N. 25° E., and S. 45° W.; desc. 220 ft. over N. slope.
	9.15 Ravine, drains N. 49° W.; asc. 85 ft. over SW. slope.
	13.45 Spur, slopes N. 85° W.; desc. 85 ft. over NW. slope.
	16.00 Ravine, drains N. 70° W.; asc. 5 ft. along W. slope.