

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the South Boundary,  
T. 20 S., R. 4 W., Willamette Meridian, Oregon

15272

CHAINS

(Restoring the survey by Harvey Gordon,  
Deputy Surveyor, in 1854)

Beginning at the cor. of tps. 20 and 21 S., Rs. 3 and 4 W.

N. 89° 42' W., bet. secs. 1 and 36, marking and blazing  
the true line.

Descend 20 ft. over W. slope, through moderate timber  
and undergrowth.

5.00 Saddle, in ridge, bears N. 65° W. and S. 65° E.; asc.  
50 ft. over SE. slope.

16.00 Spur, slopes S.; desc. 35 ft. over SW. slope.

24.98 Intersect a local property cor., established and recorded  
by Wiljo E. Green, RLS No. 563, for the Oregon State  
Board of Forestry, in 1970, monumented with an iron pipe,  
2 1/2 ins. diam., firmly set, projecting 4 ins. above  
ground, with brass cap mkd.

	SW
S 36	PROP
T 20 S	COR
R 4 W S1	
T 21 S	
R 4 W	
RS 563	

from which

A fir, 8 ins. diam., bears S. 29° W., 56 lks.  
dist., with scribe marks BT visible on open  
blaze.

A fir, 10 ins. diam., bears N. 33° W., 48 lks.  
dist., with scribe marks SW Prop Cor S36 RS 563  
viaible on open blaze.

26.20 Draw, drains S. 30° E.; asc. 100 ft. over SE. slope.

32.10 Power transmission line, bears N. 40° W. and S. 40° E.

33.30 Dirt road, 15 lks. wide bears NW. and SE.

39.30 Wire fence, bears N. and S.

39.95 The 1/4 sec. cor. of secs. 1 and 36, perpetuated and re-  
corded by Wiljo E. Green, RLS No. 563, for the Oregon  
State Board of Forestry, in 1970, monumented with an  
iron pipe, 2 1/2 ins. diam., firmly set, projecting 4 ins.  
above ground, with brass cap mkd.

1/	S 36
4	S 1
	1970

from which the remains of the original bearing tree

A root hole, bears S. 67° W., 67 lks. dist., with  
a down cedar alongside, 24 ins. diam., with  
scribe marks 1/4 S visible on open blaze. (Record,  
redwood)

and bearing trees mkd. by Green