

County Surveyor's Record, Douglas County, Oregon

15273

Dependent Resurvey of the South Boundary,
T. 20 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 5 ins. diam., bears S. 55° W., 37 1/2 lks. dist., with scribe marks 1/4 S1 BT visible on open blaze.

A fir, 10 ins. diam., bears N. 65 1/2° W., 58 lks. dist., with scribe marks 1/4 S36 BT RS 563 visible on open blaze.

and the remains of bearing trees of which I have no record.

A root hole, bears N. 10° W., 4 lks. dist., with a down fir alongside, 25 ins. diam., with scribe marks BT visible on opened blaze.

A cedar snag, 36 ins. diam., bears S. 84 1/4° E., 48 lks. dist., with scribe marks R S S visible on open blaze.

and a new bearing tree

A hemlock, 13 ins. diam., bears N. 19 1/2° E., 44 lks. dist., mkd. 1/4 S36 BT.

From this point, a corner of wire fences, bears N. 71° E., 0.560 chs. dist., with fences extending S. and W.

Add marks T20S R4W T21S 1971 to brass cap.

S. 89° 59' W., beginning new measurement.

Ascend 35 ft. over E. slope.

- 4.00 Spur, slopes S.; desc. 65 ft. over SW. slope.
- 13.30 Dirt road, 15 lks. wide, bears N. and S.
- 41.95 Underground gas transmission line, bears N. and S.
- 18.10 Creek, 2 lks. wide, course S.; asc. 20 ft. over E. slope.
- 19.91 Point for the W 1/16 sec. cor. of secs. 1 and 36.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 4 W
W 1/16 S 36
 S 1
T 21 S
1971

from which

A fir, 13 ins. diam., bears N. 12° E., 40 lks. dist., mkd. W 1/16 S36 BT.

A fir, 12 ins. diam., bears S. 79° W., 53 lks. dist., mkd. W 1/16 S1 BT.

From this point, a locally established cor., bears N. 45° W., 0.135 chs. dist., monumented with a cedar stake 2 x 3 ins., loosely set, projecting 8 ins. above ground, mkd. 1/16 S on W. and RS on S. faces, from which bearing trees of which I have no record: