

County Surveyor's Record, Douglas County, Oregon

15274

Dependent Resurvey of the South Boundary
T. 20 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 25 ins. diam., bears S. 1° E.,
69 lks. dist., with healed blaze.

A cedar, 35 ins. diam., bears S. 57° W., 80 lks.
dist., with scribe mark R visible on open blaze.

From this point, a corner of wire fences, bears N. 60° W.,
48 lks. dist., with fences extending E. and S.

Ascend 105 ft. over E. slope.

20.30 Wire fence, bears N. and S.

30.15 Spur, slopes S. 20° E.; desc. 100 ft. over SW. slope.

38.30 Dirt road, 10 lks. wide, bears N. 65° W., and S. 65° E.

39.00 Draw, drains S.; continue gradual descent over SW. slope.

39.82 The cor. of secs. 1, 2, 35, and 36, perpetuated by person
(s) unknown, monumented with an unmarked sandstone, 15 x
9 x 8 ins., firmly set 10 ins. in the ground, from which
the remains of the original bearing trees:

A sawed fir stump, 33 ins. diam., bears S. 14° W.,
50 lks. dist., no marks visible.

A cedar snag, 12 ins. diam., bears N. 25° W., 82
lks. dist., with healed blaze.

and a bearing tree mkd. by A. D. Collier, County
Surveyor, in 1912.

A fir, 20 ins. diam., bears N. 56° E., 9 lks.
dist., with healed double blaze.

and bearing trees mkd. by Weyerhaeuser Timber Co., in
1958

A fir, 15 ins. diam., bears S. 46 1/2° E., 28 1/2 lks.
dist., with a nail with "W" embossed on the head,
at base.

A sawed fir stump, 33 ins. diam., bears S. 5 1/2° W.,
50 lks. dist., with a nail with "W" embossed on
the head, at base.

A fir, 45 ins. diam., bears N. 42 1/2° W., 47 lks.
dist., with a nail with "W" embossed on the head,
at base.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins.
in the ground, with brass cap mkd.

T 20 S R 4 W	
S 35	S 36
S 2	S 1
T 21 S	
1971	

from which new bearing trees

A cedar, 10 ins. diam., bears N. 21° E., 25 lks.
dist., mkd. T20S R4W S36 BT.