

# County Surveyor's Record, Douglas County, Oregon

15276

Dependent Resurvey of the South Boundary,  
T. 20 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

T 20 S R 4 W  
1/4 S 35  
4 S 2  
T 21 S  
1971

*FD OK  
10/94  
M120-70*

from which a new bearing tree

A fir, 13 ins. diam., bears N. 56° W., 78 1/2 lks. dist., mkd. 1/4 S35 BT.

Reset iron pipe alongside iron post.

S. 89° 36' W., beginning new measurement.

Ascend 35 ft. over SE. slope.

- 3.30 Dirt road, 15 lks. wide, bears NE. and SW.
- 4.70 Ridge, bears NE. and SW.; desc. 420 ft. over NW. slope.
- 8.50 Dirt road, 15 lks. wide, bears N. 70° E. and S. 70° W.
- 13.60 Dirt road, 15 lks. wide, bears NW. and SE.; thence desc. over SW. slope.
- 39.64 The cor. of secs. 2, 3, 34 and 35, perpetuated and recorded by V. R. Tracy, Deputy County Surveyor, in 1968, monumented with an iron pipe, 1 in. diam., firmly set, projecting 12 ins. above ground, with brass cap mkd.

DOUGLAS COUNTY SURVEYORS OFFICE

R T 20 S  
4 S 34 | S 35  
W S 3 | S 2  
T 21 S  
1969

*FD OK  
10/94  
M120-70*

from which the remains of the original bearing trees

A fir snag, 37 ins. diam., bears N. 61° E., 71 lks. dist., with scribe marks 5 S visible on opened blaze and a nail with "W" embossed on the head, at base.

A sawed fir stump, 40 ins. diam., bears S. 20° E., 208 lks. dist., no marks visible.

and bearing trees mkd. by Wyerhaeuser Timber Co., in 1958, and re-marked by Tracy, in 1968

A fir, 18 ins. diam., bears N. 35° E., 15 lks. dist., with scribe marks T20S R4W S35 DCS BT visible on open double blaze.

A fir, 15 ins. diam., bears S. 60° E., 27 lks. dist., with scribe marks T21S R4W S2 DCS BT visible on open double blaze and a nail with "W" embossed on the head, at base.

A fir, 12 ins. diam., bears S. 25° W., 16 1/2 lks. dist., with scribe marks T21S R4W S3 DCS BT visible on open double blaze and a nail with "W" embossed on the head, at base.