

County Surveyor's Record, Douglas County, Oregon

15277

Dependent Resurvey of the South Boundary,
T. 20 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 13 ins. diam., bears N. 71° W., 17 1/2 lks. dist., with scribe marks T20S R4W S34 DCS BT visible on open double blaze and a nail with "W" embossed on the head, at base.

Land, mountainous.
Soil, rocky clay.
Timber, fir, cedar, hemlock, madrone, maple, alder, yew, and chinquapin; undergrowth, salal, poison oak, vine maple, arrowwood, hazel, Oregon grape, blackberry, and fern.

S. 89° 55' W., bet. secs. 3 and 34.

Descend 145 ft. over SW. slope, through moderate timber and undergrowth.

11.50 Draw, drains SW.; desc. 120 ft. over SW. slope.

23.60 Creek, 6 lks. wide, course NW.; asc. 85 ft. over E. slope.

40.07 Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 4 W
1/4 S 34
S 3
T 21 S
1971

from which

A fir, 6 ins. diam., bears S. 34 1/2° E., 25 1/2 lks. dist., mkd. 1/4 S3 BT.

A fir, 8 ins. diam., bears S. 79 1/2° W., 40 lks. dist., mkd. 1/4 S3 BT.

Set a 6 ft. steel fence post alongside iron post.

Ascend 100 ft. over E. slope.

53.00 Ridge, bears NE. and SW.; desc. 90 ft. over SW. slope.

54.00 Dirt road, 10 lks. wide, bears N. and S.

80.14 The cor. of secs. 3, 4, 33, and 34, perpetuated and recorded by Weyerhaeuser Timber Co., in 1958, monumented with an iron pipe, 5/8 ins. diam., firmly set, projecting 1 in. above ground, from which the remains of the original bearing trees:

A decayed fir stump, 18 ins. diam., bears N. 2° E., 14 lks. dist., with scribe marks BT visible on open blaze. (Record, N. 8° W.)

A sawed and decayed fir stump, 18 ins. diam., bears S. 28° W., 11 lks. dist., no marks visible. (Record, S. 30° W.)