

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of the South Boundary
T. 20 S., R. 4 W., Willamette Meridian, Oregon

15278

CHAINS

and bearing trees mkd. by Weyerhaeuser Timber Co.

A fir, 12 ins. diam., bears N. 69 1/2° E., 79 lks. dist., with a nail with "W" embossed on the head, at base.

A fir, 17 ins. diam., bears S. 49° E., 30 lks. dist., with healed lower blaze.

A fir, 15 ins. diam., bears N. 70 3/4° W., 107 lks. dist., with healed lower blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 4 W
S 33 | S 34
S 4 | S 3
T 21 S
1971

FD OK PER PEEL
M110-2 4-90
FD OK 1-91
M111-62

from which new bearing trees

A fir, 6 ins. diam., bears N. 49 1/2° E., 59 lks. dist., mkd. T20S R4W S34 BT.

A fir, 13 ins. diam., bears S. 19° W., 143 1/2 lks. dist., mkd. T21S R4W S4 BT.

A fir, 9 ins. diam., bears N. 39 1/2° W., 66 lks. dist., mkd. T20S R4W S33 BT.

Reset iron pipe alongside iron post.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, hemlock, madrone, maple, alder, yew, and chinquapin; undergrowth, salal, poison oak, vine maple, arrowwood, hazel, Oregon grape, blackberry, and fern.

S. 89° 39' W., bet. secs. 4 and 33.

Descend 115 ft. over SW. slope, through moderate timber and dense undergrowth.

14.30 Creek, 1 lk. wide, course S. 20° W.; asc. 35 ft. over SE. slope.

17.00 Spur, slopes S. 15° W.; desc. 65 ft. over W. slope.

20.015 Point for the E 1/16 sec. cor. of secs. 4 and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 4 W
E 1/16 | S 33
S 4
T 21 S
1971

FD OK PER PEEL
M110-2 4-90

from which