

County Surveyor's Record, Douglas County, Oregon

15279

Dependent Resurvey of the South Boundary,
T 20 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A fir, 16 ins. diam., bears N. 28° E., 25 lks.
dist., mkd. E 1/16 S33 BT.

A fir, 6 ins. diam., bears S. 38 1/2° W., 15 lks.
dist., mkd. E 1/16 S4 BT.

Descend 100 ft. over W. slope.

24.25 Creek, 15 lks. wide, course NW.; asc. 130 ft. over NE.
slope.

26.50 Swamp, 30 lks. wide, drains NW.; continue ascent over
NE. slope.

34.90 Gravelled road, 20 lks. wide, bears NW. and SW.

40.03 Point for the 1/4 sec. cor. of secs. 4 and 33, at propor-
tionate distance; there is no remaining evidence of the
original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 20 S R 4 W
1/4 S 33
 S 4
T 21 S
1971

FOOK PER PEEL
M110-2 4-90
FOOK 1-91
M111-62

from which

A fir, 10 ins. diam., bears S. 9° W., 27 lks.
dist., mkd. 1/4 S4 BT.

A fir, 12 ins. diam., bears N. 70° W., 20 1/2 lks.
dist., mkd. 1/4 S33 BT.

Ascend 70 ft. over NE. slope.

44.70 Creek, 1 lk wide, course N. 40° E.; asc. 5 ft. over
NE. slope.

52.60 Spur, slopes N. 80° W.; desc. 45 ft. over W. slope.

57.40 Draw, drains N. 30° E.; asc. 40 ft. over NE. slope.

60.045 Point for the W 1/16 sec. cor. of secs. 4 and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, with brass cap mkd.

W T 20 S R 4 W
S 1/16 S 33
 S 4
T 21 S
1971

FOOK PER PEEL
M110-2 4-90

from which

A fir, 8 ins. diam., bears N. 25 1/2° E., 18 lks.
dist., mkd. W. 1/16 S33 BT.

A hemlock, 8 ins. diam., bears S. 24 1/2° W., 29 lks.
dist., mkd. W 1/16 S4 BT.

Ascend 15 ft. over NE. slope.