County Surveyor's Record, Douglas County, Oregon

15281 Dependent Resurvey of the South Boundary, T. 20 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 20 S R 4 W
1/4 S 32 / S 5
T 21 S
1971

from which

A fir, 10 ins. diam., bears N. 23 1/2° E., 15 1/2 lks. dist., mkd. 1/4 S32 BT.

A fir, 11 ins. diam., bears S. 18 1/2° W., 22 1/2 lks. dist., mkd. 1/4 S35 BT.

Descend 50 ft. over NW. slope.

45.85 Creek, 1 lk. wide, course N. 20° W.; asc. 30 ft. over NE. slope.

47.80 Spur, slopes NW.; desc. 220 ft. over SW. slope.

60.55 Creek, 2 lks. wide, course N. 40° W.;asc. 20 ft. over NE. slope.

63.70 Creek, 4 lks. wide, course N. 40° E.; asc. 150 ft. over SE. slope.

73.45 Spur, slopes N. 30° E.; desc. 10 ft. over NW. slope.

79.70 The cor. of secs. 5, 6, 31, and 32, perpetuated and recorded by the Douglas County Surveyor, in 1968, monumented with an iron pipe, 1 in. diam., firmly set, projecting 4 ins. above ground, with brass cap mkd.

D.C.S.O.
T 20 S
S 31 | S 32
S 6 | S 5
T 21 S
1968-366
R 4 W

Fd. OK 11-92 BY ROBERTS M 116-48

from which the remains of the original bearing trees

A decayed fir stump, size indeterminate, bears N. 7° E., 49 lks. dist., with scribe marks 4 S BT visible on decayed blaze.

A fir snag, 13 ins. diam., bears S. 14° E., 58 lks. dist., with illegible scribe marks visible on lower blaze. (Record, 61 lks. to face)

A fir, 20 ins. diam., bears S. 43° W., 90 lks. dist., no marks visible. (Record, 87 lks. to face)

and bearing trees mkd. by Weyerhaeuser Timber Co., in 1958

A fir, 20 ins. diam., bears N. 67° E., 136 1/2 lks. dist., with healed lower blaze.

A fir, 15 ins. diam., bears S. 28° E., 68 lks. dist., with healed lower blaze.