

# County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,  
T. 24 S., R. 7 W., Willamette Meridian, Oregon

15286

**CHAINS**

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 24 S R 7 W  
1/4  $\frac{S\ 34}{S\ 3}$   
T 25 S  
1973

from which new bearing trees

A fir, 24 ins. diam., bears N. 56° W., 39 lks. dist., mkd. 1/4 S34 BT.

A hemlock, 10 ins. diam., bears S. 18 1/2° E., 26 lks. dist., mkd. 1/4 S3 BT.

S. 89° 32' W., bet. secs. 3 and 34, marking and blazing the true line.

Ascend 820 ft. over broken SE. slope, through heavy timber and dense undergrowth.

27.15 Top of ascent, slopes N.; desc. 110 ft. over W. slope.

36.44 True point for the closing cor. of secs. 33 and 34, on the N. bdy of sec. 3, T. 25 S., R. 7 W., hereinafter described.

39.54 The cor. of secs. 3 and 4 only, on the N. bdy. of T. 25 S., R. 7 W., determined at record bearing and distance from the remains of the original bearing trees:

A burned fir snag, 25 ins. diam., bears N. 43° E., 22 lks. dist., with fragmentary scribe marks visible on opened blaze.

and a bearing tree mkd. by Zirpel, in 1958

A sawed cedar stump, 28 ins. diam., bears S. 31° W., 32 1/2 lks. dist., with scribe marks T25S R7W S4 BT visible on open blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 14 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

T 24 S R 7 W  
 $\frac{S\ 33}{S\ 4\ S\ 3}$   
T 25 S  
1973

from which new bearing trees

A fir, 7 ins. diam., bears S. 12 1/2° E., 31 1/2 lks. dist., mkd. T25S R7W S3 BT.

A fir, 8 ins. diam., bears S. 81° W., 61 1/2 lks. dist., mkd. T25S R7W S4 BT.

Land, mountainous.  
Soil, rocky clay loam.