

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon


15288

CHAINS

30.03

Point for the witness meander cor.

Set an iron post, 28 ins. lon, 2 1/2 ins. diam, 26 ins. in the ground, with brass cap mkd.



from which

A triple myrtle, 23 ins. diam., bears S. 2° W.,
40 lks. dist., mkd. X BT.

No suitable tree available within limits in sec. 13.

Ascend 50 ft. over NE. slope.

39.25

The original closing cor. of secs. 23 and 24, on the S. bdy. of sec. 13, perpetuated by Milo Godfrey, Deputy County Surveyor, in 1964, monumented with an iron pipe, 1 in. diam., firmly set, protruding 8 ins. above ground, from which the remains of the original bearing trees:

A fir, 50 ins. diam., bears N. 80° E., 34 lks. dist., with scribe mark BT visible on opened blaze.


A root hole, bears S. 39° W., 27 lks. dist., with a down fir alongside, size indeterminate, no marks visible.

and a bearing tree mkd. by Godfrey

A fir, 22 ins. diam., bears S. 27° W., 62 1/2 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.



from which a new bearing tree

A fir, 6 ins. diam., bears S. 13° E., 42 1/2 lks. dist., mkd. T24S R7W S24 CC BT.

Ascend 5 ft. over NE. slope.

39.55

Spur, slopes N.; desc. 15 ft. over NW. slope.

40.49

The cor. of secs. 13 and 14 only, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.