

# County Surveyor's Record, Douglas County, Oregon

15289

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 24 S., R 7 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 24 S  
S 14 | S 13  
S 23  
R 7 W  
1958

from which the remains of the original bearing trees

A fir stump, 36 ins. diam., bears S. 48° W., 36 lks. dist., with scribe mark S visible on opened blaze.

And bearing trees mkd. by Byron

A fir, 20 ins. diam., bears N. 22° E., 70 lks. dist., with healed blaze.

A cedar, 17 ins. diam., bears N. 63° W., 96 1/2 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, madrone, alder, and maple; undergrowth, vine maple, fern salal, hazel, ceanothus, and poison oak.

From the cor. of secs. 23, 24, 25, and 26, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1 1/2 ins. dian., firmly set, protruding 14 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

S 23 | S 24  
S 26 | S 25  
T 24 S R 7 W  
1958

from which the remains of the original bearing trees

A root hole, bears N. 4° E., 49 lks. dist., with a down fir alongside, 32 ins. diam., with healed blaze.

A cedar, 40 ins. diam., bears S. 62° E. 88 lks. dist., with healed blaze.

A cedar, 32 ins. diam., bears S. 79° W., 97 lks. dist., with healed blaze.

and bearing trees mkd. by Byron

A fir, 16 ins. diam., bears S. 42° W., 14 lks. dist., with healed blaze.

A fir, 10 ins. diam., bears N. 17° W., 6 1/2 lks. dist., with healed blaze.

and a new bearing tree

A fir, 10 ins. diam., bears N. 29 1/2° E., 26 lks. dist., mkd. T24S R7W S24 BT.

N. 89° 44' W., bet. secs. 23 and 26.

Descend 220 ft. over broken NW. slope, through heavy timber and dense undergrowth.