

County Surveyor's Record, Douglas County, Oregon

15290

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

7.40 Dirt road, 20 lks, wide, in curve, bears N. 15° E. and S. 5° W.

18.20 Creek, 2 lks. wide, course N. 30° E.; asc. 140 ft. over E. slope.

21.10 Spur, slopes NE.; desc. 35 ft. over NW. slope.

24.20 Bottom of descent, slopes N.; asc. 45 ft. over NE. slope.

28.50 Spur, slopes N.; desc. 30 ft. over NW. slope.

31.50 Bottom of descent, slopes N.; asc. 200 ft. over E. slope.

40.07 The 1/4 sec. cor. of sec. 23 and 26, monumented with the original sandstone, 14 x 12 x 10 ins., firmly set, 6 ins. in the ground, mkd. 1/4 on N. face, from which the original bearing trees:

A fir, 48 ins. diam., bears N. 16° W., 11 lks. dist., with healed blaze. (Record, N. 20° W.)

A fir, 36 ins. diam., bears S. 55° E., 15 lks. dist., with healed blaze. (Record, S. 46° E.)

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

1/4 S 23
 S 26
T 24 S R 7 W
1973

Deposit corner stone alongside iron post.

N. 89° 48' W., beginning new measurement.

Ascend 430 ft. over E. slope.

11.50 Ridge, bears N. and S.; desc. 180 ft. over NW. slope.

15.00 Dirt road, 10 lks. wide, bears N. 50° E. and S. 50° W.

19.35 Dirt road, 10 lks. wide, bears N. 60° W. and S. 60° E.

27.35 Creek, 1 lk. wide, course N. 25° W.; asc. 205 ft. over NE. slope.

34.05 Dirt road, 10 lks. wide, bears N. 20° W. and S. 20° E.

34.35 Spur, slopes N.; desc. 70 ft. over NW. slope.

40.12 The cor. of secs. 22, 23, 26, and 27, perpetuated by Vernon R. Tracy, Deputy County Surveyor, in 1966, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S
S 22 | S 23
S 27 | S 26
R 7 W
1966

from which the remains of the original bearing trees