

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 15292
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{1}{4} S 14$
 T 24 S R 7 W
 1973

from which

A chinquapin, 24ins. diam., bears N. 56° E., 7 1/2 lks. dist., mkd. 1/4 S14 BT.

A fir, 21 ins. diam., bears N. 73° W., 51 1/2 lks. dist., mkd. 1/4 S14 BT.

Descend 120 ft. over NW. slope.

46.50 Ravine, drains N. 10° W.; asc. 345 ft. over NE. slope.

56.70 Ridge, bears N. and S.; desc. 390 ft. over NW. slope.

72.40 Creek, 1 lk. wide, course N. 35° W.; asc. 120 ft. over NE. slope.

76.20 Spur, slopes N.; desc. 50 ft. over NW. slope.

78.55 Ravine, drains N. 30° E.; asc. 15 ft. over NE. slope.

78.70 The original closing cor. of secs. 22 and 23, on the S. bdy. of sec. 14, determined at record bearing and distance from the remains of the original bearing trees:

A fir, 42 ins. diam., bears S. 69° E., 142 lks. dist., with healed blaze.

A decayed fir stump, 60 ins. diam., bears S. 66° W., 79 lks. dist., no marks visible on decayed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$\frac{S 14}{S 22 \quad S 23}$
 T 24 S R 7 W
 C C
 1973

from which a new bearing tree

A hemlock 17 ins. diam, bears S. 30° W., 67 1/2 lks. dist., mkd. T24S R7W S22 CC BT.

Ascend 95 ft. over NE. slope.

80.32 The cor. of secs. 14 and 15 only, perpetuated by James W. Byron, Deputy County Surveyor, in 1958, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, in the remains of the original corner tree, a decayed chinquapin stump, size indeterminate, no marks visible, with brass cap mkd.