

County Surveyor's Record, Douglas County, Oregon

15293

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

COUNTY SURVEYORS OFFICE

T 24 S
S 15 | S 14
S 22
R 7 W
1958

from which the remains of the original bearing trees

A fir stump, 40 ins. diam., bears N. 45° E., 34 lks. dist., with scribe marks BT visible on opened blaze.

A fir snag, 35 ins. diam., bears S. 68° W., 23 lks. dist., no marks visible.

A decayed fir stump, size indeterminate, bears N. 74° W., 50 lks. dist., no marks visible.

and bearing trees mkd. by Byron

A fir, 12 ins. diam., bears N. 46° E., 94 lks. dist., with healed blaze.

A fir, 28 ins. diam., bears N. 48 1/2° W., 31 lks. dist., with healed blaze.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, cedar, hemlock, yew alder, chinquapin, maple, and madrone; undergrowth, vine maple, hazel, salal, fern, salmonberry, ocean spray, and poison oak.

From the cor. of secs. 22, 23, 26, and 27.

N. 0° 01' E., bet. secs. 22 and 23.

Descend 545 ft. over N. slope, through heavy timber and dense undergrowth.

3.40 Gravelled road, 10 lks. wide, bears N. 75° W., and S. 75° E.

10.60 Dirt road, 10 lks. wide, bears N. 35° E. and S. 35° W.

20.90 Creek, 1 lk. wide, course N. 35° W.; desc. 20 ft. over N slope.

23.10 Creek, 1 lk. wide, course S. 70° W.; asc. 490 ft. over SW. slope.

39.82 Point for the 1/4 sec. cor. of secs. 22 and 23, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mdk.

1/4
S 22 | S 23
T 24 S R 7 W
1973

from which

A fir, 16 ins. diam., bears N. 86° E., 20 1/2 lks. dist., mkd. 1/4 S23 BT.