

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 15294
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 17 ins. diam., bears N. 24 1/2° W., 59 lks. dist., mkd. 1/4 S22 BT.

Ascend 230 ft. over SW. slope.

57.50 Spur, slopes NW.; desc. 680 ft. over N. slope.

78.70 Ravine, drains N. 30° E.; desc. 20 ft. over NW slope.

79.49 The original closing cor. of secs. 22 and 23, hereinbefore described.

From this point, the cor. of secs. 14 and 15 only, on the N. bdy. of sec. 22, bears N. 89° 40' W., 1.62 chs. dist., hereinbefore described.

Land, mountainous.

Soil, rocky clay loam

Timber, fir, hemlock, cedar, alder, maple, madrone, yew, and chinquapin; undergrowth, vine maple, salal, fern, ocean spray, salmonberry, and poison oak.

From the cor. of secs. 27, 28, 33, and 34, perpetuated by James W. Byron, Deputy County Surveyor, in 1959, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 12 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 24 S R 7 W

S 28 | S 27

S 33 | S 34

SEC. COR.

1959

FD OK
Mark Smalley
9/96 4124-27

from which the remaining original bearing trees

A fir, 50 ins. diam., bears S. 70° E., 11 lks. dist., with scribe mark B visible on opened blaze; re-marked by Byron in 1959, with healed blaze. (Record, S. 50° E.)

A fir, 60 ins. diam., bears N. 80° W., 95 lks. dist., no marks visible on opened blaze.

and bearing trees mkd. by Byron, in 1959

A fir, 16 ins. diam., bears S. 52° W., 49 lks. dist., with healed blaze.

A fir, 24 ins. diam., bears N. 79° W., 73 lks. dist., with healed blaze.

No other suitable trees available within limits.

South, bet. secs. 33 and 34.

Ascend 125 ft. over NW. slope, through scattering timber and dense undergrowth.

7.75 Spur, slopes W.; desc. 25 ft. over SW. slope.

10.20 Ravine, drains N. 55° W.; asc. 165 ft. over NW. slope.

20.07 The N 1/16 sec. cor. of secs. 33 and 34, established and recorded by Bruce Shaner, Registered Engineer No. 4906, in 1972, monumented with an iron post, 1 1/2 ins. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.