

County Surveyor's Record, Douglas County, Oregon

15295

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R.7 W., Willamette Meridian, Oregon

CHAINS

T 24 S R 7 W W.M.
N 1/16
S 33|S 34
1972

from which bearing trees mkd. by Shaner

A fir, 8 ins. diam., bears S. 55° E., 26 1/2 lks. dist., with scribe marks N 1/16 S34 BT visible on open blaze.

A fir, 17 ins. diam., bears N. 35° W., 24 lks. dist., with scribe marks N 1/16 S33 BT visible on open blaze.

S. 0° 01' E., beginning new measurement.

Ascend 250 ft. over NW, slope.

20.05

The 1/4 sec. cor. of secs. 33 and 34, perpetuated and recorded by Bruce Shaner, Registered Engineer, No. 4906, in 1972, monumented with an iron post, 28 ins. long, 1 1/2 ins. diam., firmly set, protruding 8 ins. above ground, with brass cap mkd.

T 24 S R 7 W W.M.
S 33|S 34
1/4 S
1972

from which the remaining original bearing tree

A fir, 33 ins. diam., bears S. 2° W., 26 lks. dist., with fragmentary scribe marks visible on opened blaze.

and a new bearing tree

A fir, 11 ins. diam., bears S. 62 1/2° E., 81 1/2 lks. dist., mkd. 1/4 S34 BT.

S. 0° 12' E., beginning new measurement.

Ascend 75 ft. over NW. slope.

23.50

Spur, slopes W.; desc. 10 ft. over SW. slope.

28.10

Head of ravine, drains N. 35° W.; asc. 140 ft. over N. slope.

40.035

Intersect the N. bdy. of sec. 3, T. 25 S., R. 7 W.

True point for closing cor. of secs. 33 and 34.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

C C
T 24 S | R 7 W
S 33 | S 34
S 3
T 25 S R 7 W
1973

from which