

County Surveyor's Record, Douglas County, Oregon

15297

Dependent Resurvey, Portion of Subdivisional Lines,
T. 24 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

from which

A fir, 13 ins. diam., bears N. 46 1/2° E., 48 lks. dist., mkd. 1/4 S28 BT.

A fir, 15 ins. diam., bears S. 50° W., 34 lks. dist., mkd. 1/4 S33 BT.

From this corner, a locally established point bears S. 89° E., 0.693 chs. dist., monumented with an iron pipe, 1 in. diam., firmly set, protruding 30 ins. above ground.

Descend 420 ft. over W. slope.

57.22

Point for the meander cor. of secs. 28 and 33, on the right bank of the Umpqua River, at proportionate distance; there is no remaining evidence of the original corner. This point falls in oil surfaced road, 20 lks. wide, bears N. 15° E. and S. 15° W.

Set a brass tablet, 3 1/2 ins. diam., 3 ins. stem, in a drill hole, in oil surfaced road, with top mkd.

	T 24 S
MC	S 28
/	S 33
	R 7 W
	1973

from which

A fir, 26 ins. diam., bears N. 76 1/2° E., 97 lks. dist., mkd. T24S R7W S28 MC BT.

A fir, 18 ins. diam., bears S. 81 1/2° E., 86 lks. dist., mkd. T24S R7W S33 MC BT.

Descend 5 ft. over W. slope.

57.45

Right bank of the Umpqua River, bears N. 15° E., and S. 15° W., course N. 15° E.; thence across river.

64.99

True point for the meander cor. of secs. 28 and 33, on the left bank of the Umpqua River, at proportionate distance, falls in the Umpqua River, where it is impracticable to establish a permanent monument.

Ascend 10 ft. over SE. slope.

66.35

Left bank of the Umpqua River, bears N. 15° E. and S. 15° W.; asc. 5 ft. over SE. slope.

66.56

Point selected for the witness meander cor. of secs. 28 and 33, on the left bank of the Umpqua River.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

→	WC	
	T 24 S	
	S 28	
	S 33	/ MC
	R 7 W	
	1973	

from which