

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the South Boundary,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

15302

CHAINS

Beginning at the cor. of secs. 2, 3, 34, and 35, determined at record bearing and distance from the remains of the original bearing trees:

A root hole, bears N. 40° E., 708 lks. dist.

A black oak, 59 ins. diam., bears N. 89° W., 1,197 lks. dist., with scribe marks BT visible on opened blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 34 ins. in the ground, with top 6 ins. below surface, with brass cap mkd.

T 25 S R 7 W
 $\frac{S\ 34\ S\ 35}{S\ 3\ S\ 2}$
 T 26 S
 1975

from which new bearing trees

A fir, 20 ins. diam., bears N. 65 1/2° E., 553 lks. dist., mkd. T25S R7W S35 BT.

A fir, 12 ins. diam., bears S. 80° W., 1,011 lks. dist., mkd. T26S R7W S3 BT.

No other suitable trees available within limits

Corner is located in open cultivated field.

S. 89° 57' W., bet. secs. 3 and 34, marking the true line.

Ascend 50 ft. over cultivated field.

13.70 Woven wire fence, bears N. and S.

39.96 Point for the 1/4 sec. cor. of secs. 3 and 34, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 42 ins. in the ground, with top 14 ins. below surface, with brass cap mkd.

T 25 S R 7 W
 $\frac{1}{4} \frac{S\ 34}{S\ 3}$
 T 26 S
 1975

from which

A twin cedar, 14 ins. diam., bears N. 23 1/2° E., 592 1/2 lks. dist., mkd. 1/4 S34 BT.

A fir, 22 ins. diam., bears S. 6° E., 195 lks. dist., mkd. 1/4 S3 BT.

Ascend 135 ft. over cultivated field.

47.30 Barbed wire fence, 5 strand, bears N. and S.