

County Surveyor's Record, Douglas County, Oregon

15303

Dependent Resurvey of a Portion of the South Boundary,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

79.92

The cor. of secs. 3, 4, 33, and 34, perpetuated and re-
corded by Edwin S. Woodford, Deputy County Surveyor, in
1947, when remains of the original corner accessories
were in existence. The cor. was subsequently perpetuated
and recorded by Michael S. Stone, Deputy County Surveyor,
in 1966, and monumented with an iron post, 1 in. diam.,
firmly set, projecting 12 ins. above ground, with brass
cap mkd.

COUNTY SURVEYORS OFFICE

T 25 S R 7 W
S 33 | S 34
S 4 | S 3
T 26 S
1966

from which the remains of a bearing tree mkd. by Woodford

A sawed fir stump, 24 ins. diam., bears S. 30 1/2° W.,
13 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 14 ins. diam., bears S. 66° E., 145 1/2 lks.
dist., mkd. T26S R7W S3 BT.

No other suitable trees available within limits.

Corner is located at junction of fences, extending S.
and W.

Land, rolling fields.

Soil, clay loam.

Timber, fir, cedar, and oak; undergrowth, poison oak,
salal, and blackberry.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 25 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by Dennis Hathorn,
U. S. Deputy Surveyor, in 1855,
and the survey by William H. Byars,
U. S. Deputy Surveyor, in 1874)

From the cor. of secs. 2, 3, 34, and 35, on the S. bdy.
of the Tp.

N. 0° 11' W., bet. secs. 34 and 35, marking and blazing
the true line.

Descend 55 ft. over cultivated field.

3.60 Woven wire fence, bears E. and W.

12.20 Woven wire fence, bears E. and W.

19.65 Creek, 10 lks. wide, course E.; asc. 15 ft. over nearly
level land.

25.00 Barbed wire fence, 5 strands, bears E. and W., leave
cultivated field, enter open pasture land, edge bears
same as fence.

25.45 Creek, 2 lks. wide, course E.; asc. 30 ft. over gently
S. slope.