

County Surveyor's Record, Douglas County, Oregon

15305

Dependent Resurvey, Portion of Subdivisional Lines,
T. 25 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A black oak, 34 ins. diam., bears S. 16 1/2° E., 422 lks. dist., mkd. T25S R7W S35 BT.

A fir, 13 ins. diam., bears N. 29 1/2° W., 225 lks. dist., mkd. T25S R7W S27 BT.

No suitable tree available within limits in SW. quadrant.

Land, rolling fields.

Soil, clay loam.

Timber, fir, cedar, and oak; undergrowth, poison oak and blackberry.

From the cor. of secs. 4, 5, 32, and 33, on the S. bdy. of the Tp., perpetuated and recorded by Vernon Tracy, Deputy County Surveyor, in 1966, monumented with an iron post, 1 in. diam., firmly set, projecting 18 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 25 S		R
S 32	S 33	7
S 5	S 4	W
T 26 S		
1966		

from which the remains of the original bearing trees

A fir, 63 ins. diam., bears N. 80° E., 28 lks. dist., with scribe marks T S R7W visible on bark and with healed lower blaze.

A fir, 45 ins. diam., bears N. 50° W., 60 lks. dist., with scribe mark S visible on bark.

and bearing trees mkd. by Tracy

A fir, 25 ins. diam., bears S. 22° E., 38 lks. dist., with healed double blaze.

A fir, 9 ins. diam., bears S. 63° W., 27 lks. dist., with healed double blaze.

A maple, 10 ins. diam., bears N. 50° W., 14 lks. dist., with scribe marks T25S R7W S32 CS BT visible on open double blaze.

N. 1° 13' W., bet. secs. 32 and 33.

Ascend 330 ft. over SE. slope, through heavy timber and moderate undergrowth.

2.75 Ravine, drains S. 30° E.; asc. 270 ft. over S. slope.

15.70 Ridge, bears NE. and SW.; desc. 405 ft. over N. slope.

24.05 Gravelled road, 20 lks. wide, bears N. 30° E. and S. 30° W.

41.79 Point for the 1/4 sec. cor. of secs. 32 and 33.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

T 25 S R 7 W
1/4
S 32 S 33
1975