

# County Surveyor's Record, Douglas County, Oregon

15306

Dependent Resurvey, Portion of Subdivisional Lines,  
T. 25 S., R. 7 W., Willamette Meridian, Oregon

**CHAINS**

from which

A sawed fir stump, 20 ins. diam., bears N. 64 1/2° E.,  
18 lks. dist., mkd. 1/4 S33 BT.

A fir, 10 ins. diam., bears N. 46° W., 95 1/2 lks.  
dist., mkd. 1/4 S32 BT.

Descend 470 ft. over NW. slope.

64.40 Creek, 1 lk. wide, course N. 55° W.; desc. 15 ft. over  
NW. slope.

69.70 Creek, 1 lk. wide, course N. 55° W.; asc. 100 ft. over  
SW. slope.

83.58 The cor. of secs. 28, 29, 32, and 33, monumented with an  
iron post, 2 1/2 ins. diam., firmly set, projecting 10 ins.  
above ground, and in a mound of stone, 2 ft. base, 1 ft.  
high, with brass cap mkd.

T 25 S R 7 W  
S 29 | S 28  
S 32 | S 33  
1968

from which bearing trees mkd. by Heydon, in 1896

A cedar, 40 ins. diam., bears N. 11° E., 322 lks.  
dist., no marks visible on opened blaze.

A fir, 45 ins. diam., bears S. 29 1/2° W., 170 lks.  
dist., with healed blaze.

A fir, 54 ins. diam., bears S. 83° W., 165 lks.  
dist., with healed blaze. (Record, 152 lks.)

and bearing trees mkd. by Roseberry and Garrison, in 1969

A fir, 18 ins. diam., bears S. 83 1/2° E., 27 lks.  
dist., with healed blaze.

A fir, 24 ins. diam., bears N. 49° W., 41 1/2 lks.  
dist., with healed blaze.

Land mountainous.

Soil, rocky clay loam.

Timber, fir, hemlock, cedar, madrone, maple, chinquapin,  
and alder; undergrowth, salal, Oregon Grape, poison oak,  
young timber, vine maple, arrowwood, hazel, and fern.

From the cor. of secs. 5, 6, 31, and 32, on the S. Bdy.  
of the Tp., monumented with an iron post, 2 1/2 ins. diam.  
firmly set, projecting 4 ins. above ground, with brass  
cap mkd.

T 25 S R 7 W  
S 31 | S 32  
S 6 | S 5  
T 26 S  
1971

from which bearing trees mkd. by Richard C. Grant,  
Registered Engineer, No. 2807, in 1958