

County Surveyor's Record, Douglas County, Oregon

15307

Dependent Resurvey, Portion of Subdivisional Lines
T. 25 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 27 ins. diam., bears N. 1° E., 43 lks. dist., with scribe marks S32 T25S R7W BT visible on bark blaze. (Record, N. 2 1/2° E.)

A fir, 13 ins. diam., bears S. 30° E., 18 lks. dist., with healed blaze.

A fir, 8 ins. diam., bears S. 49° W., 26 lks. dist., with healed blaze.

A madrone, 7 ins. diam., bears N. 55° W., 9 lks. dist., with scribe marks T25S R7W visible on bark blaze.

and bearing trees mkd. by Peterson, Popken, Wofford, and Berry, in 1971

A fir, 5 ins. diam., bears N. 78° E., 43 lks. dist., with scribe marks BT visible on open lower blaze.

A fir, 38 ins. diam., bears N. 12° W., 66 1/2 lks. dist., with scribe marks BT visible on partially healed blaze. (Record, 72 lks.)

N. 0° 40' W., bet. secs. 31 and 32.

Ascend 10 ft. over SW. slope, through heavy timber and dense undergrowth.

1.05 Spur, slopes W.; desc. 200 ft. over NW. slope.

10.90 Creek, 5 lks. wide, course S. 60° W.; asc. 370 ft. over SE. slope.

32.45 Gravelled road, 40 lks. wide, bears N. 60° E. and S. 60° W.

34.70 Dirt road, 15 lks. wide, bears E. and W.

35.70 Ridge, bears N. 65° E. and S. 65° W.; desc. 75 ft. over NW. slope.

41.41 Point for the 1/4 sec. cor. of secs. 31 and 32, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 26 ins. in the ground, with brass cap mkd.

*Fa. OK
6/9 + BY DeGroot
M 119 - 33*

T 25 S R 7 W
1/4
S 31 | S 32
1975

from which

A fir, 25 ins. diam., bears N. 73 1/2° E., 41 1/2 lks. dist., mkd. 1/4 S32 BT.

A fir, 16 ins. diam., bears N. 42° W., 33 lks. dist., mkd. 1/4 S31 BT.

Descend 510 ft. over NW. slope.

63.50 Gravelled road, 30 lks. wide, bears N. 40° E. and S. 40° W.