

# County Surveyor's Record, Douglas County, Oregon

15311

T. 32 S., R. 7 W., Willamette Meridian, Oregon

## CHAINS

The following field notes are those of the dependent resurvey of a portion of the east boundary and a portion of the subdivisional lines, township 32 south, range 7 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

The east boundary of the township was surveyed by Wells Lake and George W. Hyde, in 1855.

The subdivisional lines were surveyed by William H. Byars, in 1881.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions., 1973, and the Special Instructions dated August 13, 1975, for Group Number 884, Oregon.

The directions of the lines were determined by deflections from azimuths obtained by direct solar observations.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were remonumented in their original positions. Lost corners were reestablished and remonumented at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. All lines not forming closures were measured twice. Only those lines bounding or crossing public lands were blazed.

The geographic position of the corner of sections 19, 24, 25, and 30, on the east boundary of the township, as scaled from the Canyonville, Oregon, quadrangle map, published by the United States Geological Survey in 1954 is as follows:

Latitude  $42^{\circ} 46.1' N.$       Longitude  $123^{\circ} 28.0' W.$

The mean magnetic declination is  $19^{\circ} 30' E.$

Dependent Resurvey of a Portion of the East Boundary,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon.

(Restoring the survey executed by Wells Lake and George W. Hyde, U. S. Deputy Surveyors, in 1855, and the resurvey executed by William H. Byars, U. S. Deputy Surveyor, in 1881.)

Beginning at the cor. of secs. 19, 24, 25, and 30, on the E. bdy. of the Tp., perpetuated and recorded by William B. Paulin, RLS No. 552, in 1962, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, from which the remains of the original bearing trees:

A decayed fir stump, size indeterminate, bears  
S.  $15^{\circ} E.$ , 28 lks. dist., no marks visible.

A madrone, 18 ins. diam., bears South, 38 1/2 lks.  
dist., no marks visible on opened blaze.  
(Record, S.  $10^{\circ} W.$ )