

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the East Boundary,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

15312

CHAINS

and the remains of bearing trees mkd. by Paulin

A root hole, bears N. 22 1/2° E., 45 1/2 lks. dist., with a down madrone alongside, 11 ins. diam., with scribe mark W visible on open blaze.

A chinquapin, 11 ins. diam., bears S. 44 1/4° E., 57 1/2 lks. dist., with scribe marks S30 T32S R6W BT visible on open double blaze.

A madrone, 9 ins. diam., bears S. 10° W., 78 lks. dist., with scribe marks S25 T32S R7W visible on open blaze.

A chinquapin, 12 ins. diam., bears N. 81 1/2° W., 18 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, directly atop iron pipe, with brass cap mkd.

T 32 S
R 7 W R 6 W
S 24 S 19
S 25 S 30
1976

*FO. OK
1/16/92
DCSO
C.S. 64/23*

from which a new bearing tree

A chinquapin, 6 ins. diam., bears N. 11 3/4° E., 13 1/2 lks. dist., mkd. T32S R6W S19 BT.

N. 0° 14' E., bet. secs. 19 and 24, marking and blazing the true line.

Descend 120 ft. over NE. slope, along east edge of clearcut.

16.20 Creek, 3 lks. wide, course S. 70° E.; asc. 710 ft. over SE. slope.

36.80 Spur ridge, bears N. 70° W. and S. 70° E.; desc. 35 ft. over NE. slope.

39.48 Point for the 1/4 sec. cor. of secs. 19 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S
1/4
R 7 W R 6 W
S 24 S 19
1976

from which

A fir, 13 ins. diam., bears N. 54 1/2° E., 11 1/2 lks. dist., mkd. 1/4 S19 BT.

A fir, 12 ins. diam., bears N. 75° W., 22 1/2 lks. dist., mkd. 1/4 S24 BT.