

# County Surveyor's Record, Douglas County, Oregon

15313

Dependent Resurvey of a Portion of the East Boundary,  
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

Descend 5 ft. over NE. slope.

39.90 Ravine, drains S. 70° E.; asc. 125 ft. over SE. slope.

46.10 Leave edge of clearcut, enter light timber and heavy undergrowth.

48.50 Spur, slopes S. 50° E.; desc. 130 ft. over NE. slope.

57.90 Bottom of descent, slopes E.; asc. 45 ft. over SE. slope.

59.22 Point for the N 1/16 sec. cor. of secs. 19 and 24.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd,

N 1/16  
S 24 | S 19  
1976

from which

A fir, 20 ins. diam., bears N. 74° E., 34 lks. dist., mkd. N. 1/16 S19 BT.

A madrone, 9 ins. diam., bears N. 79 1/2° W., 80 lks. dist., mkd. N 1/16 S24 BT on bark.

Ascend 55 ft. over SE. slope.

62.85 Creek, 1 lk. wide, course S. 50° E.; asc. 425 ft. over broken SE. slope.

78.96 Point for the cor. of secs. 13, 18, 19, and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 20 ins. in the ground, and in a mound of stone, 2 ft. base, to top, with brass cap mkd.

T 32 S  
R 7 W R 6 W  
S 13 | S 18  
S 24 | S 19  
1976

from which

A fir, 32 ins. diam., bears N. 68 1/2° E., 81 1/2 lks. dist., mkd. T32S R6W S18 BT.

A fir, 20 ins. diam., bears S. 45° E., 47 lks. dist., mkd. T32S R6W S19 BT.

A fir, 28 ins. diam., bears S. 44 1/2° W., 157 1/2 lks. dist., mkd. T32S R7W S24 BT.

A fir, 15 ins. diam., bears N. 23 1/2° W., 30 lks. dist., mkd. T32S R7W S13 BT.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, pine, oak, madrone, dogwood, and cedar; undergrowth, arrowwood, fern, poison oak, hazel, and fir reproduction