

County Surveyor's Record, Douglas County, Oregon

15314

Dependent Resurvey of a Portion of the East Boundary,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

N. 0° 14' E., bet. secs. 13 and 18.

Ascend 190 ft. over broken SE. slope, through scattered timber and dense undergrowth.

9.70 Spur, slopes S. 70° E.; asc. 265 ft. over SE. slope.

19.74 Point for the S 1/16 sec. cor. of secs. 13 and 18.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.

S 1/16
S 13 | S 18
1976

from which

A fir, 15 ins. diam., bears N. 61° E., 43 lks.
dist., mkd. S 1/16 S18 BT.

A fir, 18 ins. diam., bears S. 22° W., 28 lks.
dist., mkd. S 1/16 S13 BT.

Ascend 175 ft. over SE. slope.

31.25 Ridge, bears N. 40° E. and S. 40° W.; desc. 230 ft. over NW. slope.

39.48 Point for the 1/4 sec. cor. of secs. 13 and 18, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S
1/4
R 7 W | R 6 W
S 13 | S 18
1976

from which

A fir, 13 ins. diam., bears N. 55° E., 17 1/2 lks.
dist., mkd. 1/4 S18 BT.

A fir, 10 ins. diam., bears S. 65° W., 48 lks.
dist., mkd. 1/4 S13 BT.

Descend 785 ft. over NW. slope.

68.10 Bottom of descent, slopes W.; asc. 60 ft. over NW. slope.

73.60 Spur, slopes N. 60° W.; desc. 205 ft. over N. slope.

78.96 The cor. of secs. 7, 12, 13, and 18, perpetuated and recorded by John M. Powell, Deputy County Surveyor, in 1965, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 15 ins. above ground, with brass cap mkd.

T 32 S R 6 W
R S 12 | S 7
7 S 13 | S 18
W 1965