

County Surveyor's Record, Douglas County, Oregon

15315

Dependent Resurvey of a Portion of the East Boundary
T. 32 S. , R. 7 W., Willamette Meridian, Oregon

CHAINS

from which the remains of the original bearing trees

A root hole, bears S. 8° E., 18 lks. dist., with a down fir alongside, 40 ins. diam., no marks visible.

A fir, 27 ins. diam., bears N. 63° W., 71 lks. dist., with healed blaze.

and the remains of bearing trees mkd. by Powell

A fir snag, 13 ins. diam., bears N. 72° E., 141 1/2 lks. dist., with scribe marks T32S R6W S7 CS BT visible on open double blaze.

A fir, 31 ins. diam., bears S. 85° E., 58 1/2 lks. dist., with healed double blaze.

A fir, 8 ins. diam., bears S. 76° W., 87 1/2 lks. dist., with healed double blaze.

and a new bearing tree

A fir, 50 ins. diam., bears N. 69 1/2° E., 96 lks. dist., mkd. T32S R6W S7 BT.

Land, mountainous.

Soil, rocky clay loam

Timber, fir, pine, oak, madrone, and dogwood; undergrowth, arrowwood, fern, poison oak, hazel, and fir and pine reproduction.

Dependent Resurvey of a Portion of the Subdivisional Lines
T. 32 S., R. 7 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars,
U. S. Deputy Surveyor, in 1881)

From the cor. of secs. 23, 24, 25, and 26, perpetuated and recorded by Vernon R. Tracy, Deputy County Surveyor, in 1970, monumented with an iron pipe, 1 1/2 ins. diam., firmly set, projecting 10 ins. above ground, with brass cap mkd.

T 32 S	
S 23	S 24
S 26	S 25
R 7 W	
1970	

from which the remains of the original bearing trees

A fir, 21 ins. diam., bears N. 21 1/2° E., 17 lks. dist., with healed blaze. (Record, N. 18° E.)

A fir, 33 ins. diam., bears S. 48 1/2° E., 71 lks. dist., with fragmentary scribe marks visible on bark and with healed blaze. (Record, S. 45° E.)

A madrone root crown, bears S. 50° W., 18 lks. dist., no marks visible. (Record, 22lks.)

and a bearing tree mkd. by Tracy