

County Surveyor's Record, Douglas County, Oregon

15316

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

A fir, 45 ins. diam., bears N. 22° W., 65 lks. dist., with scribe marks T32S R7W S23 CS BT visible on bark.

and a new bearing tree

A chinquapin, 7 ins. diam., bears S. 76 1/4° W., 37 1/2 lks. dist., mkd. T32S R7W S26 BT.

N. 3° 08' E., bet. secs. 23 and 24, marking and blazing the true line.

Descend 140 ft. over NE. slope, through moderate timber and heavy undergrowth, along east edge of clearcut.

10.50 Bottom of descent, slopes E.; asc. 115 ft. over broken SE. slope, also enter timber, edge bears E. and S.

20.065 Point for the S 1/16 sec. cor. of secs. 23 and 24.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

S 1/16
S 23 | S 24
1976

from which

A fir, 25 ins. diam., bears N. 76 1/2° E., 55 lks. dist., mkd. S 1/16 S24 BT.

A fir, 12 ins. diam., bears N. 10° W., 44 1/2 lks. dist., mkd. S 1/16 S23 BT.

Corner is located in head of ravine, drains S. 25° E.

Ascend 415 ft. over SE. slope.

40.13 Point for the 1/4 sec. cor. of secs. 23 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins. in the ground, with brass cap mkd.

T 32 S R 7 W
1/4
S 23 | S 24
1976

from which

A fir, 22 ins. diam., bears S. 47° E., 46 lks. dist., mkd. 1/4 S24 BT.

A fir, 17 ins. diam., bears N. 53° W., 24 lks. dist., mkd. 1/4 S23 BT.

Ascend 150 ft. over SE. slope.

46.80 Ridge, bears N. 40° E. and S. 40° W.; thence along broken W. slope.

49.80 Spur, slopes N. 80° W.; desc. 90 ft. over broken NW. slope.