

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 S., R. 7 W., Willamette Meridian, Oregon

15318

CHAINS

A fir, 12 ins. diam., bears N. 3 1/2° E., 112 lks. dist., mkd. E 1/16 S13 BT.

A fir, 13 ins. diam., bears S. 63° E., 22 lks. dist., mkd. E 1/16 S24 BT.

Descend 655 ft. over SW. slope.

37.75 Creek, 1 lk. wide, course S. 25° E.; asc. 120 ft over SE. slope, also enter moderate timber.

38.56 Point for the 1/4 sec. cor. of secs. 13 and 24, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 32 S R 7 W
1/4 S 13
S 24
1976

from which

A fir, 7 ins. diam., bears North, 24 lks. dist., mkd. 1/4 S13 BT.

A fir, 10 ins. diam., bears S 13 1/2° W., 69 1/2 lks dist., mkd. 1/4 S24 BT.

Ascend 455 ft. over steep rocky SE. slope.

60.75 Ridge, bears N. 20° E. and S. 10° W.; desc. 375 ft. over NW. slope.

71.40 Spur, slopes N. 50° W.; desc. 95 ft. over NW. slope.

77.12 The cor. of secs. 13, 14, 23, and 24.

Land, mountainous.

Soil, rocky clay loam.

Timber, fir, oak, madrone, pine, and chinquapin; undergrowth, hazel, arrowwood, poison oak, and oak reproduction.

N. 0° 04' W., bet. secs. 13 and 14.

Descend 100 ft. over NW. slope, through light timber and dense undergrowth.

2.25 Ravine, drains N. 50° W.; asc. 50 ft. over SW. slope.

15.25 Spur, slopes N. 80° W.; desc. 430 ft. over steep NW. slope.

30.85 Creek, 2 lks. wide, course S. 65° W.; asc. 350 ft. over SW. slope.

40.07 Point for the 1/4 sec. cor. of secs. 13 and 14, at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 16 ins. in the ground, and in a mound of stone, 3 ft. base, to top, with brass cap mkd.