

County Surveyor's Record, Douglas County, Oregon

15319

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

T 32 S R 7 W
1/4
S 14 | S 13
1976

from which

A pine, 27 ins. diam., bears S. 78° E., 94 1/2 lks. dist., mkd. 1/4 S13 BT.

A cedar, 7 ins. diam., bears S. 23 3/4° W., 46 lks. dist., mkd. 1/4 S14 BT.

Ascend 5 ft. over S.W. slope.

41.75 Spur, slopes S. 50° W.; desc. 45 ft. over NW. slope.

45.75 Ravine, drains S. 70° W.; asc. 320 ft. over SW. slope.

46.20 Abandoned dirt road, 15 lks. wide, bears N. 60° E. and S. 60° W.

60.00 Ridge, bears S. 40° E. and N. 40° W., also dirt road, 20 lks. wide, bears same; desc. 85 ft. over NE. slope.

70.20 Bottom of descent, slopes W.; asc. 80 ft. over SW. slope.

78.90 Spur, slopes S. 85° E.; desc. 60 ft. over NE. slope.

80.14 The cor. of secs. 11, 12, 13, and 14, perpetuated and recorded by Howard W. Johnstone, RLS No. 498, in 1970, monumented with a 5/8 in. iron rod, firmly set, projecting 6 ins. above ground, with 1 1/2 ins. aluminum cap mkd.

T 32 S R
11 | 12 7
14 | 13 W

from which the remains of the original bearing trees

A cedar, 30 ins. diam., bears S. 66 1/2° E., 26 lks. dist., with scribe marks T S visible on bark. (Record, S. 78° E.)

A madrone cluster, bears S. 60° W., 20 lks. dist., no marks visible.

and bearing trees mkd. by Johnstone

A fir, 11 ins. diam., bears N. 73° E., 28 lks. dist. with pitched over double blaze.

A fir, 18 ins. diam., bears S. 47 1/2° E., 6 1/2 lks. dist., with pitched over double blaze.

A fir, 20 ins. diam., bears S. 71° W., 4 1/2 lks. dist., with pitched over double blaze.

A fir, 18 ins. diam., bears N. 11 1/2° W., 41 lks. dist., with pitched over double blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.