

County Surveyor's Record, Douglas County, Oregon

15320

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 7 W., Willamette Meridian, Oregon

CHAINS

T 32 S R 7 W
 $\frac{S 11 | S 12}{S 14 | S 13}$
 1976 \

Reset iron rod alongside iron post.

Land, mountainous.
 Soil, rocky clay loam.
 Timber, pine, fir, cedar, madrone, and chinquapin; under-
 growth, arrowwood, hazel, poison oak, and fern.

From the cor. of secs. 13, 14, 23, and 24.

S. 87° 18' W., bet. secs. 14 and 23.

Descend 100 ft. over broken NW. slope, through light timbe- and dense undergrowth.

11.70 Spur, slopes N. 10° W.; desc. 85 ft. over NW. slope.

15.60 Bottom of descent, slopes NW.; asc. 45 ft. over NE. slope.

18.90 Spur, slopes N. 20° W.; desc. 135 ft. over NW. slope.

28.50 Spur, slopes N. 20° W.; desc. 70 ft. over NW. slope.

30.05 Bottom of descent, slopes NW.; asc. 30 ft. over NE. slope.

38.40 The 1/4 sec. cor. of secs. 14 and 23, perpetuated and re-
 corded by Vernon R. Tracy, Deputy County Surveyor, in
 1970, monumented with an iron pipe, 1 in. diam., firmly
 set, projecting 10 ins. above ground, with brass cap mkd.

T 32 S R 7 W
 $\frac{1}{4} \frac{S 14}{S 23}$
 1970

from which the original bearing trees

A fir, 32 ins. diam., bears N. 50° E., 23 lks.
 dist., with fragmentary scribe marks visible on
 bark.

A madrone, 23 ins. diam., bears S. 60° E., 14 lks.
 dist., with original blaze opened and decayed,
 no marks visible. This tree was reblazed and
 marked 1/4 S23 CS BT by Tracy.

and a bearing tree mkd. by Tracy

A pine, 36 ins. diam.; bears S. 37 1/2° W., 44 lks.
 dist., with scribe marks 1/4 S23 CS BT visible
 on open blaze.

Land, mountainous.
 Soil, rocky clay loam.
 Timber, pine, fir, madrone, and cedar; undergrowth, hazel,
 arrowwood, and poison oak.