

# County Surveyor's Record, Douglas County, Oregon

15323

T. 31 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

The following field notes are those of the dependent resurvey of a portion of the subdivisional lines, township 31 south, range 9 west, Willamette Meridian, Oregon.

The history of surveys pertaining to this resurvey, is as follows:

The subdivisional lines were surveyed by William H. Byars, in 1901.

The survey was executed in accordance with the specifications as set forth in the Manual of Surveying Instructions, 1947, and the Special Instructions dated July 19, 1973, for Group Number 822, Oregon.

The direction of the line was determined by the solar transit method.

Preliminary to the resurvey, the lines of the original survey were retraced and search was made for all corners and other calls of the record. Identified corners were renumbered in their original positions. Lost corners were reestablished and renumbered at proportionate positions, based on the official record. The retracement data were thoroughly verified and only the true line field notes are given herein. The line resurveyed was measured twice to preclude error and was fully blazed.

The geographic position of the corner of sections 27, 28, 33, and 34, as scaled from the Bone Bountain, Oregon, quadrangle map, published by the United States Geological Survey, in 1954, is as follows:

Latitude 42° 50.3' N.    Longitude 123° 45.6' W.

The mean magnetic declination is 19° 00'E.

Dependent Resurvey of a Portion of the Subdivisional Lines,  
T. 31 S., R. 9 W., Willamette Meridian, Oregon

(Restoring the survey by William H. Byars,  
U. S. Deputy Surveyor, in 1901)

Beginning at the cor. of secs. 27, 28, 33, and 34, perpetuated and recorded by the County Surveyor, in 1967, monumented with an iron post, 1 in. diam., firmly set, protruding 6 ins. above ground, with brass cap mkd.

COUNTY SURVEYORS OFFICE

T 31 S R 9 W  
 S 28 | S 27  
 S 33 | S 34  
 1967

from which the remains of the original bearing trees

A sawed fir stump, 34 ins. diam., bears N. 15° E., 53 1/2 lks. dist., with scribe marks R9W S27 visible on partially healed double blaze. (Record, 52 lks.)

A sawed fir stump, 31 ins. diam., bears S. 65° E., 12 lks. dist., with healed double blaze. (Record, S. 60° E.)