

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, 15324
T. 31 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A fir, 19 ins. diam., bears S. 31° W., 25 lks. dist., with healed double blaze. (Record, S. 32° W.)

A sawed fir stump, 17 ins. diam., bears N. 57° W., 67 lks. dist., with illegible scribe marks visible on partially healed double blaze. (Record, N. 58° W.)

and the remains of a bearing tree mkd. by the County Surveyor

A root hole, bears S. 25° E., 68 lks. dist., with a down sawed fir stump alongside, 40 ins. diam. with scribe marks T31S R9W S34 CS BT visible on partially healed blaze.

and new bearing trees

A fir, 4 ins. diam., bears N. 52 1/4° E., 72 1/2 lks. dist., mkd. X BT.

A fir, 6 ins. diam., bears S. 27 1/2° E., 99 lks. dist., mkd. X BT.

A fir, 4 ins. diam., bears N. 17° W., 42 1/2 lks. dist., mkd. X BT.

N. 0° 02' W., bet. secs. 27 and 28, marking and blazing the true line.

Descend 220 ft. over NE. slope, through moderate young timber and low undergrowth, across logged area.

- 2.60 Gravelled road, 20 lks. wide, bears N.W. and SE.
 - 8.00 Same road, bears N. 25° E. and S. 25° W.
 - 19.35 Dirt road, 15 lks. wide, bears NW. and S. 20° E., in curve; enter heavy timber and dense undergrowth, edge bears same as road.
 - 26.50 Spur, slopes N. 10° E.; desc. 170 ft. over general NW. slope.
 - 32.25 Spur, slopes N. 55° W.; desc. 365 ft. over steep N. slope.
 - 37.60 Gravelled road, 20 lks. wide, bears N. 75° E. and S. 75° W.
 - 40.02 Point for the 1/4 sec. cor. of secs. 27 and 28, at proportionate distance; there is no remaining evidence of the original corner.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

T 31 S R 9 W
1/4
S 28 | S 27
1973

from which

A fir, 55 ins. diam., bears S. 72° E., 43 lks. dist., mkd. 1/4 S27 BT.