

# County Surveyor's Record, Douglas County, Oregon

15325

Dependent Resurvey, Portion of Subdivisional Lines  
T. 31 S., R. 9 W., Willamette Meridian, Oregon

CHAINS

A sawed fir stump, 48 ins. diam., bears N. 74° W.,  
28 lks. dist., mkd. 1/4 S28 BT.

No other suitable tree available within limits in  
sec. 28.

Descend 45 ft. over steep N. slope.

41.30 West Fork of Cow Creek, 30 lks. wide, course N. 80° E.;  
asc. 240 ft. over steep S. slope.

48.50 Ravine, drains S. 35° E.; asc. 310 ft. over steep SW.  
slope.

55.80 Gravelled road, 25 lks. wide, bears N. 35° E. and  
S. 55° E., in curve.

59.80 Spur, slopes SE.; asc. 75 ft. over gradual SE. slope.

71.50 Top of ascent, slopes E.; desc. 20 ft. over NE. slope.

73.90 Spring seepage, drains S. 80° E.; asc. 15 ft. over SE.  
slope.

76.50 Top of ascent, slopes E.; desc. 20 ft. along E. slope.

80.04 The cor. of secs. 21, 22, 27, and 28, determined at re-  
cord bearing and distance from the remains of the  
original bearing trees:

A burned and decayed fir stump, 16 ins. diam.,  
bears N. 68° W., 100 lks. dist., no marks  
visible on a badly burned and decayed detached  
blaze lying alongside.

At the corner point

Set an iron post, 28 ins. long 2 1/2 ins. diam., 24 ins.  
in the ground, with brass cap mkd.

T	31	S	R	9	W
	S	21	S	22	
	S	28	S	27	
	1973				

from which new bearing trees

A fir, 13 ins. diam. bears N. 17 1/2° E., 22 lks.  
dist., mkd. T31S R9W S22 BT.

A fir, 14 ins. diam., bears S. 64 3/4° E., 68 lks.  
dist., mkd. T31S R9W S27 BT.

A fir, 10 ins. diam., bears S. 62 1/2° W., 42 1/2 lks.  
dist., mkd. T31S R9W S28 BT.

A fir, 9 ins. diam., bears N. 45° W., 47 1/2 lks.  
dist., mkd. T31S R9W S21 BT.

Land, mountainous.

Soil, rocky clay.

Timber, fir, cedar, chinquapin, madrone, yew, and alder;  
undergrowth, salal, vine maple, hazel, Oregon grape,  
fern, and ceanothus.