

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey of a Portion of the West Boundary, 15329
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

1 1/2 ins. diam., firmly set, 46 ins. in the ground, from which the remains of the bearing trees mkd. by Stewart:

A burned and decayed fir stump, 33 ins. diam., bears N. 16° E., 279 lks. dist., no marks visible.

A burned and decayed fir stump, size indeterminate, bears N. 71° E., 329 lks. dist., no marks visible.

and bearing trees mkd. by Wendroth

A sawed live oak stump, 15 ins. diam., bears N. 4 1/4° E., 160 1/2 lks. dist., with healed double blaze.

A fir, 25 ins. diam., bears S. 60 1/2° E., 91 lks. dist., with healed double blaze.

and a bearing tree and bearing object mkd. by the Douglas County Surveyor, in 1966

A fir, 8 ins. diam., bears N. 2° E., 132 1/2 lks. dist., with illegible scribe marks visible on partially healed and pitched over blaze.

A power pole, No. E3457, bears N. 21 1/2° W., 36 1/2 lks. dist.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 36 ins. in the ground, with brass cap mkd.

T 32 S
R 5 W R 4 W
S 12 S 7
S 13 S 18
1971

Deposit iron rod alongside iron post.

N. 0° 02' W., bet. secs. 7 and 12, marking and blazing the true line.

Descend 5 ft. over gentle NE. slope, along driveway, bears N. and S.

0.80 Asphaltic surfaced road, 30 lks. wide, bears N. 80° W., and S. 80° E.; enter moderate timber and undergrowth.

4.20 Starvout Creek, 25 lks. wide, course N. 55° W.; asc. 245 ft. over SW. slope.

17.50 Spur, slopes NW.; desc. 70 ft. over NW. slope.

20.00 The S 1/16 sec. cor. of secs. 7 and 12, established and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, monumented with an iron rod, 1 in. diam., protruding 6 ins. above ground, firmly set, from which the remains of the bearing tree mkd. by Stewart:

A madrone stump, 16 ins. diam., bears S. 39° E., 45 lks. dist., no marks visible on decayed blaze.