

# County Surveyor's Record, Douglas County, Oregon

15330

Dependent Resurvey, Portion of W. Bdy., T. 32 S., R. 4 W.,  
Willamette Meridian, Oregon

CHAINS

and bearing trees mkd. by George J. Wendroth, Deputy  
County Surveyor, in 1957

A madrone, 7 ins. diam., bears S. 34° W., 35 1/2 lks.  
dist., with scribe marks 6 CS BT visible on  
partially healed blaze.

A madrone, 5 ins. diam., bears N. 80° W., 27 1/2 lks.  
dist., with scribe marks 1/16 CS BT visible on  
partially healed blaze.

N. 0° 06' W., beginning new measurement.

Descend 175 ft. over NW. slope changing to N. slope.

5.90 Wire fence, bears NE. and SW.

6.60 Asphaltic surfaced road, 30 lks. wide, bears NE. and SW.

7.50 Creek, 2 lks. wide, course N. 80° W.; continue over  
nearly level ground, across open field.

20.01 The 1/4 sec. cor. of secs. 7 and 12, perpetuated and  
recorded by G. G. Stewart, Deputy County Surveyor, in  
1922, from the remaining original 1854 bearing tree  
which is no longer in existence; subsequently perpetu-  
ated and recorded by James W. Byron, Deputy County  
Surveyor, in 1956, monumented with an iron pipe, 1 1/2 ins.  
diam., protruding 4 ins. above ground, firmly set, with  
brass cap mkd.

COUNTY SURVEYORS OFFICE  
T 32 S  
1/4 S 12 | 7  
R 5 W | R 4 W  
1956

from which bearing tree mkd. by Stewart

A fir, 29 ins. diam., bears N. 56° E., 218 lks.  
dist., with healed blaze. This tree was re-  
scribed 1/4 S7 CS BT by Byron in 1956.

and a bearing tree mkd. by Byron in 1956

A live oak, 15 ins. diam., bears N. 84° E., 247 lks.  
dist., with healed blaze.

No suitable bearing tree available within limits in  
sec. 12.

The corner is located at corner of fences extending S.  
and W.

N. 0° 32' E, beginning new measurement.

Descend 10 ft. over NW. slope, across open field.

7.00 Wire fence, bears E. and W.

8.90 Cow Creek, 70 lks. wide, course S. 60° W.; asc. 100 ft.  
over SE. slope.

10.60 Asphaltic surfaced road, 30 lks. wide, bears N. 60° E.,  
and S. 60° W.