

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of W. Bdy., T. 32 S., R. 4 W., **15331**
Willamette Meridian, Oregon

CHAINS				
13.00	Power line, bears N. 80° E., and S. 80° W.			
13.80	Leave open field, edge bears NE. and SW.; enter heavy timber and dense undergrowth, along E. edge of logged area.			
16.80	Abandoned irrigation ditch, 3 lks. wide, course S. 70° W.			
20.00	<p>The N 1/16 sec. cor. of secs. 7 and 12, established and recorded by G. G. Stewart, Deputy County Surveyor, in 1922; subsequently perpetuated and recorded by Marvin C. Ramsey, Registered Land Surveyor No. 404, in 1967, monumented with an iron pipe, 1 in. diam., protruding 6 ins. above the ground, firmly set, with attached washer mkd. RS404, from which the remains of the bearing tree mkd.</p> <p style="padding-left: 40px;">A sawed fir stump, 20 ins. diam., bears S. 86 3/4° W., 9 lks. dist., no marks remaining.</p> <p>and bearing trees mkd. by Ramsey</p> <p style="padding-left: 40px;">A fir, 10 ins. diam., bears N. 10 1/2° E., 22 lks. dist., with pitched over blaze.</p> <p style="padding-left: 40px;">A fir, 20 ins. diam., bears S. 80° W., 30 1/2 lks. dist., with pitched over blaze.</p> <p>At the corner point</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over the iron pipe, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto;"> <tr><td style="padding: 0 10px;">N 1/16</td></tr> <tr><td style="padding: 0 10px;">S 12 S 7</td></tr> <tr><td style="padding: 0 10px;">1971</td></tr> </table> </div> <hr style="width: 20%; margin: 10px auto;"/> <p>N. 0° 38' E., beginning new measurement.</p> <p>Ascend 600 ft. over SE. slope.</p>	N 1/16	S 12 S 7	1971
N 1/16				
S 12 S 7				
1971				
19.96	<p>The cor. of secs. 1, 6, 7, and 12, perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, from two original 1854 bearing trees, monumented with an iron pipe, 1 in. diam., protruding 4 ins. above the ground, firmly set, alongside of which is lying a basalt stone reported by John H. Markham, Registered Engineer No. 2880, in 1951, 16 x 12 x 10 ins., with no marks visible, at record bearing from the remains of the original 1854 bearing trees:</p> <p style="padding-left: 40px;">A burned out ponderosa pine stump, size indeterminate, bears N. 55° E., 40 lks. dist., no marks remaining.</p> <p style="padding-left: 40px;">A black oak, 18 ins. diam., bears S. 31° E., 76 lks. dist., with healed double blaze.</p> <p style="padding-left: 40px;">A black oak, 20 ins. diam., bears N. 41 1/2° W., 161 lks. dist., with opened and decayed double blaze with negative scribe marks BT visible on detached piece lying alongside. (Record, 170 lks.)</p> <p>and bearing trees mkd. by Stewart</p>			