

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines,
T. 32 S., R. 4 W., Willamette Meridain, Oregon

15333

CHAINS

A sawed fir stump, 26 ins. diam., bears N. 52° W.,
26 lks. dist., no marks remaining.

and a bearing tree mkd. by George J. Wendroth, Deputy
County Surveyor, in 1946

A sawed fir stump, 28 ins. diam., bears S. 38° W.,
11 1/2 lks. dist., with scribe marks S18 CS BT
visible on open double blaze.

and bearing trees mkd. by the Douglas County Surveyor,
in 1970

A fir, 6 ins. diam., bears N. 9° E., 38 lks.
dist., with pitched over blaze.

A fir, 23 ins. diam., bears N. 73° W., 9 1/2 lks.
dist., with scribe marks T32S R4W S18 CS BT
visible on partially healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 22 ins.
in the ground, with brass cap mkd.

T 32 S R 4 W
 S 18
 S 20
 1971

From this point, a point established and recorded by
George J. Wendroth, Deputy County Surveyor, in 1946,
monumented with an iron pipe, 1 1/2 ins. diam., protruding
6 ins. above the ground, firmly set, bears S. 65 3/4° E.,
0.06 chs. dist.

N. 0° 35' W., along the E. bdy. of sec. 18 marking and
blazing the true line.

Descend 35 ft. over N. slope, through moderate timber
and dense undergrowth, across logged area.

1.05 Creek, 1 lk. wide, course N. 60° E.; asc. 55 ft. over
SE. slope.

4.50 Top of ascent, slopes E.; desc. 80 ft. over NE. slope.

10.24 True point for the closing cor. of secs. 17 and 20, on
E. bdy. of sec. 18, hereinafter described.

Descend 75 ft. over NE. slope.

11.55 Dirt road, 15 lks. wide, bears N. 50° W., and S. 50° E.

14.25 Power and telephone line, bears N. 80° W., and S. 80° E.

19.78 From this point, a point established and recorded by
George J. Wendroth, Deputy County Surveyor, in 1946,
bears West, 0.115 chs. dist., monumented with a wooden
stake, 2 ins. diam.-protruding 24 ins. above the ground,
firmly set, from which bearing trees mkd. by Wendroth:

A chinquapin snag, 12 ins. diam., bears S. 45 1/4° W.,
94 lks. dist., with scribe marks 1/16 S18 CS BT
visible on partially healed double blaze.

An alder snag, 10 ins. diam., bears N. 43 1/2° W., 63 lks.
dist., with scribe marks 1/16 S18 CS visible
on partially healed double blaze.