

# County Surveyor's Record, Douglas County, Oregon

**15334**

Dependent Resurvey, Portion of Subdivisional Lines  
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS							
	Descend 30 ft. over NE. slope.						
24.70	Starvout Creek, 20 lks. wide, course N. 65° W.; asc. 8 ft. over gradual S. slope of valley bottom.						
30.21	<p>Point for the S 1/16 sec. cor. of sec. 17 only.</p> <p>Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.</p> <div style="text-align: center; margin: 10px 0;"> <table style="margin: auto; border: none;"> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 1/16</td> <td style="padding-left: 5px;"> </td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">S 17</td> <td style="padding-left: 5px;"> </td> </tr> <tr> <td style="border-right: 1px solid black; padding-right: 5px;">1971</td> <td style="padding-left: 5px;"> </td> </tr> </table> </div> <p>from which bearing trees mkd. by George J. Wendroth, Deputy County Surveyor, in 1946,</p> <p style="margin-left: 40px;">A fir, 20 ins. diam., bears N. 25 1/2° E., 184 1/2 lks. dist., with healed blaze.</p> <p style="margin-left: 40px;">An apple, 20 ins. diam., bears S. 81 3/4° E., 498 lks. dist., with healed blaze.</p> <p>From this point, a point established and recorded by George J. Wendroth, Deputy County Surveyor, in 1946, bears S. 39° W., 0.125 chs. dist., monumented with an aluminum conduit pipe, 1/2 in. diam., protruding 3 ins. above ground, firmly set.</p> <p>Ascend 5 ft. over gradual S. slope of valley bottom.</p>	S 1/16		S 17		1971	
S 1/16							
S 17							
1971							
35.90	Asphaltic surfaced road, 30 lks. wide, bears N. 70° W. and S. 70° E.; also leave valley bottom, edge bears same; asc. 75 ft. over SW. slope.						
36.25	Dirt road, 20 lks. wide, bears E. and W.						
40.05	<p>Point for the 1/4 sec. cor. of sec. 18 only, at proportionate distance; there is no remaining evidence of the original corner. No permanent monument established.</p> <p>From this point, a point established and recorded by George J. Wendroth, Deputy County Surveyor, in 1946, bears S. 50° W., 0.095 chs. dist., monumented with an iron pipe, 1 in. diam., protruding 6 ins. above ground, firmly set, from which bearing trees mkd. by Wendroth:</p> <p style="margin-left: 40px;">A sawed fir stump, 18 ins. diam., bears S. 16° W., 63 lks. dist., with scribe marks BT visible on open blaze.</p> <p style="margin-left: 40px;">A sawed fir stump, 41 ins. diam., bears N. 46 1/2° W., 58 lks. dist., with illegible scribe marks visible on open blaze.</p> <p>and bearing trees mkd. by Wendroth, in 1960</p> <p style="margin-left: 40px;">A cedar, 24 ins. diam., bears S. 45 1/2° W., 232 1/2 lks. dist., with scribe marks 1/4 S18 visible on partially healed double blaze.</p> <p style="margin-left: 40px;">A fir, 11 ins. diam., bears N. 15 3/4° W., 105 lks. dist., mkd. with a healed double blaze.</p> <p>Ascend 115 ft. over SW. slope, along E. edge of logged area.</p>						