

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **15335**
 T. 32 S., R. 4 W., Willamette Meridain, Oregon

CHAINS

- 45.15 Spur, slopes SW.; desc. 10 ft. along W. slope.
- 46.65 Head of ravine, drains S. 60° W.; asc. 95 ft. over SW. slope.
- 50.18 Point for the 1/4 sec. cor. of sec. 17 only, at midpoint latitudinally on the W. bdy. of sec. 17.
- Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.
- T 32 S R 4 W
 | 1/4 S 17
 1971
- from which bearing trees mkd. by George J. Wendroth, Deputy County Surveyor, in 1946
- A fir, 32 ins. diam., bears N. 25 3/4° E., 13 1/2 lks. dist., with healed blaze.
- A chinquapin, 11 ins. diam., bears S. 20° E., 18 lks. dist., with scribe marks 4S S17 BT visible on partially healed blaze.
- From this point, a point established and recorded by George J. Wendroth, Deputy County Surveyor, in 1946, bears S. 64° W., 0.075 chs. dist., monumented with an iron pipe, 1 in. diam., protruding 6 ins. above ground, firmly set.
- From this same point, another point established and recorded by Wendroth, in 1946, bears S. 22° W., 0.095 chs. dist., monumented with an iron pipe, 3/4 ins. diam., protruding 6 ins. above ground, firmly set, from which bearing trees mkd. by Wendroth, in 1946:
- A chinquapin, 6 ins. diam., bears S. 47 1/2° W., 6 lks. dist., with scribe mark S visible on partially healed blaze.
- A madrone, 8 ins. diam., bears N. 32° W., 25 1/2 lks. dist., with scribe marks CS BT visible on partially healed blaze.
- Descend 10 ft. over NW. slope.
- 51.15 Ravine, drains S. 70° W.; asc. 165 ft. over SW. slope.
- 59.30 Spur, slopes SW.; asc. 40 ft. along W. slope.
- 68.00 Ravine, drains S. 50° W.; asc. 270 ft. over S. slope, changing to MW. slope.
- 80.02 The cor. of secs. 7 and 18 only, on W. bdy. of sec. 17, reestablished and recorded by George J. Wendroth, Deputy County Surveyor, in 1946, monumented with an iron pipe, 1 in. diam., protruding 10 ins. above ground, firmly set. This point is accepted as the best available evidence of the position of the original corner.
- from which bearing trees mkd. by Wendroth
- A black oak, 8 ins. diam., bears S. 15 3/4° W., 89 lks. dist., with scribe marks CS S18 CC BT visible on decayed blaze.