

County Surveyor's Record, Douglas County, Oregon

15336

Dependent Resurvey, Portion of Subdivisional Lines
T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

A black oak, 6 ins. diam., bears N. 9 1/2° W., 57 1/2 lks. dist., with healed blaze.

At the corner point

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, directly over iron pipe, with brass cap mkd.

$$\begin{array}{r} T\ 32\ S\ R\ 4\ W \\ \hline S\ 7 \quad | \quad S\ 17 \\ S\ 18 \quad | \\ \hline 1971 \end{array}$$

from which new bearing trees

A fir, 14 ins. diam., bears S. 60° W., 40 lks. dist., mkd. T32S R4W S18 BT.

A fir, 12 ins. diam., bears N. 50° W., 36 lks. dist., mkd. T32S R4W S7 BT.

Land, mountainous except for narrow valley bottom.
Soil, rocky clay.

Timber, fir, pine, cedar, oak, madrone, maple, alder, and chinquapin; undergrowth, reproduction, vine maple, salal, poison oak, Oregon grape, arrowwood, huckleberry, and manzanitz.

S. 87° 06' W., bet. secs. 7 and 18.

Descend 350 ft. over SW. slope, through moderate timber and dense undergrowth, along N. edge of partially logged area.

13.50 Ravine, drains S. 50° W.; desc. 145 ft. over SW. slope.

18.55 Ravine, drains S. 20° W.; asc. 15 ft. along S. slope.

20.12 Point for the E 1/16 sec. cor. of secs. 7 and 18

Set an iron post, 28 ins. long, 2 1/2 ins. diam., 24 ins. in the ground, with brass cap mkd.

$$\begin{array}{r} E\ 1/16 \quad \frac{S\ 7}{S\ 18} \\ \hline 1971 \end{array}$$

from which

A fir, 23 ins. diam., bears N. 50° W., 56 lks. dist., mkd. E 1/16 S7 BT.

A fir, 14 ins. diam., bears S. 45° W., 81 1/2 lks. dist., mkd. E 1/16 S18 BT.

Ascend 70 ft. along S. slope.

26.15 Spur, slopes S.; desc. 195 ft. along S. slope, changing to SW. slope.

36.30 Ravine, drains S. 50° W.; asc. 25 ft. over SE. slope.

38.80 Spur, slopes S. 20° W.; desc. 65 ft. over SW. slope.