

County Surveyor's Record, Douglas County, Oregon

Dependent Resurvey, Portion of Subdivisional Lines, **15337**
 T. 32 S., R. 4 W., Willamette Meridian, Oregon

CHAINS

40.24

The 1/4 sec. cor. of secs. 7 and 18, perpetuated and recorded by G. G. Stewart, Deputy County Surveyor, in 1922, from the original 1871 bearing trees, one of which is still in existence; subsequently perpetuated and recorded by George J. Wendroth, Registered Land Surveyor No. 5, in 1944, and as Deputy County Surveyor, in 1965, monumented with an iron pipe, 1 1/4 ins. diam., protruding 12 ins. above the ground, firmly set, with brass cap mkd.

COUNTY SURVEYORS OFFICE

1/4 SEC

7

18

DEP LS 5

1965

from which the remains of the original 1871 bearing tree

A sawed ponderosa pine stump, 22 ins. diam., bears S. 30° W., 29 lks. dist., with scribe mark S. visible on decayed blaze.

and bearing trees mkd. by Stewart

A sawed ponderosa pine stump, 30 ins. diam., bears N. 43° E., 67 lks. dist., no marks visible on decayed blaze.

and bearing trees mkd. by Wendroth, in 1944

A sawed fir stump, 24 ins. diam., bears N. 89 1/2° E., 61 lks. dist., with scribe marks CS BT visible on opened blaze.

A sawed ponderosa pine stump, 26 ins. diam., bears S. 23 1/4° E., 33 lks. dist., no marks visible on decayed blaze.

and bearing trees mkd. by Wendroth, in 1965

A fir, 20 ins. diam.- bears N. 48 1/4° W., 47 1/2 lks. dist., with healed double blaze.

A fir, 22 ins. diam., bears S. 6° E., 61 lks. dist., with pitched over double blaze.

S. 88° 08' W., beginning new measurement.

Descend 80 ft. over SW. slope, across logged area.

4.90

Ravine, drains S. 30° W.; desc. 70 ft. over SW. slope.

11.80

Corner of fences extending N., S., and W.; continue along fence in open field.

20.38

Intersect a point established and record by George J. Wendroth, Deputy County Surveyor, in 1953, monumented with an iron bar, 1 in. diam., protruding 4 ins. above ground, firmly set, from which bearing trees mkd. by Wendroth:

A shattered madrone stump, 8 ins. diam., bears N. 13 3/4° E., 30 lks. dist., alongside of which is lying a madrone, with scribe marks 1/16 S7 CS BT visible on open blaze.